

IFRM 05N37A3/S35L

Inductive proximity switch - subminiature

Article number: 11082469

overview

- 1,6 mm
- NPN break function (NC)
- connector M8
- -25 ... 75 °C
- IP 67



Technical data

general data

mounting type	flush
nominal sensing distance Sn	1,6 mm
hysteresis	2 ... 20 % of Sr
output indicator	3 port LED red

electrical data

switching frequency	< 3 kHz
voltage supply range +Vs	10 ... 30 VDC
current consumption max. (no load)	12 mA
output circuit	NPN break function (NC)
voltage drop Vd	< 2 VDC
output current	< 100 mA

electrical data

short circuit protection	yes
reverse polarity protection	yes

mechanical data

type	cylindrical threaded
material (sensing face)	LCP
housing material	stainless steel
dimension	5 mm
housing length	36 mm
connection types	connector M8
tightening torque max.	2 Nm (Front: 1,4 Nm)

ambient conditions

operating temperature	-25 ... +75 °C
protection class	IP 67

remarks

- M8 x 1 quick disconnect
- 3 port LED


2020-06-26 The product features and technical data specified do not express or imply any warranty. Technical modifications subject to change.

IFRM 05N37A3/S35L

Inductive proximity switch - subminiature

Article number: 11082469

dimension drawing



connection diagram

