

O200.GL-GW2I.72NV/A014_F040_H006

Diffuse sensors with background suppression - miniature

Article number: 11231161

overview

- Outstanding reliability and unrivalled immunity against ambient light
- Focused laser beam for small objects or gaps
- IO-Link interface independent of the switching output (Dual Channel)
- Extended parameterization options and additional diagnostic data
- Quick mounting by means of M3 threaded bushes made of stainless steel



Picture similar



Technical data

general data

type	background suppression
version	IO-Link dual channel
light source	pulsed red laser diode
sensing distance Tw	20 ... 120 mm
sensing range Tb	3 ... 132 mm
smallest object recogniz- able typ.	0,05 mm at 40 mm
alignment / soiled lens in- dicator	flashing output indicator
power on indication	LED green
output indicator	LED yellow
sensing distance adjust- ment	IO-Link
laser class	1
distance to focus	40 mm
wave length	680 nm
suppression of reciprocal influence	yes
beam type	point
alignment optical axis	< 1,5°

electrical data

response time / release time	< 0,4 ms (High Speed Mode)
jitter	< 0,21 ms (High Speed Mode)
voltage supply range +Vs	10 ... 30 VDC

electrical data

current consumption max. (no load)	20 mA (@ 10 VDC)
current consumption typ.	10 mA (@ 24 VDC)
voltage drop Vd	< 2 VDC
output function	light / dark operate
output circuit	push-pull
output current	< 50 mA
short circuit protection	yes
reverse polarity protection	yes

communication interface

baud rate	38,4 kBaud (COM 2)
adjustable parameters	switching point switching hysteresis time filters LED status indicators output logic output circuit counter operation mode deactivate the sensor element Find Me function Teach-in mode
IO-Link port type	Class A
process data length	32 Bit

Technical data

communication interface

process data structure	Bit 0 = SSC1 (presence) Bit 2 = quality Bit 3 = alarm Bit 5 = SSC4 (counter) Bit 16-31 = 16 Bit measurement
------------------------	---

interface	IO-Link V1.1
-----------	--------------

additional data	excess gain operating cycles device temperature
-----------------	---

cycle time	≥ 2,7 ms
------------	----------

mechanical data

width / diameter	8 mm
height / length	25,1 mm


mechanical data

depth	15,8 mm
type	rectangular
mechanical mounting	threaded sleeves M3 (stainless steel)
housing material	plastic (ASA, PMMA)
front (optics)	PMMA
connection types	flylead connector M8 4 pin, L=200 mm
cable characteristics	PVC / PVC 4 x 0,08 mm ²


ambient conditions

operating temperature	-20 ... +50 °C
protection class	IP 67

dimension drawing



connection diagram




laser warning

**CLASS 1 LASER
PRODUCT**


IEC 60825-1/2014

Complies with 21 CFR 1040.10 and 1040.11
except for deviations pursuant to laser
notice No. 50, dated June 24, 2007


pin assignment



beam characteristic (typically)



sensing distance diagram



hysteresis curve

