

O200.RL.C-GW2I.72NV/A014_FIN1_H006

Article number: 11231199

overview

- Extended functional reserve capacities for maximum reliability
- Object detection through smallest holes and gaps without blind area thanks to single-lens optics
- Parallel laser beam for uniform detection over the measuring range
- IO-Link interface independent of the switching output (Dual Channel)
- Extended parameterization options and additional diagnostic data
- Quick mounting by means of M3 threaded bushes made of stainless steel



Picture similar



Technical data

general data

type	retro-reflective sensor
version	single lens optics IO-Link dual channel
light source	pulsed red laser diode
actual range Sb	0,8 m
nominal range Sn	1,2 m
smallest object recogniz- able typ.	3 mm at 500 mm
polarization filter	yes
alignment / soiled lens in- dicator	flashing output indicator
output indicator	LED yellow
power on indication	LED green
sensitivity adjustment	IO-Link
laser class	1
distance to focus	parallel beam
wave length	680 nm
suppression of reciprocal influence	yes
alignment optical axis	< 1,5°

electrical data

response time / release time	< 0,2 ms (High Speed Mode)
jitter	< 0,18 ms (High Speed Mode)
voltage supply range +Vs	10 ... 30 VDC

electrical data

current consumption max. (no load)	20 mA (@ 10 VDC)
current consumption typ.	10 mA (@ 24 VDC)
voltage drop Vd	< 2 VDC
output function	light / dark operate
output circuit	push-pull
output current	< 50 mA
short circuit protection	yes
reverse polarity protection	yes

communication interface

baud rate	38,4 kBaud (COM 2)
adjustable parameters	switching point time filters LED status indicators output logic output circuit counter operation mode deactivate the sensor element Find Me function Teach-in mode
IO-Link port type	Class A
process data length	32 Bit

Technical data

communication interface

process data structure	Bit 0 = SSC1 (presence) Bit 2 = quality Bit 3 = alarm Bit 5 = SSC4 (counter) Bit 16-31 = 16 Bit measurement
------------------------	---

interface	IO-Link V1.1
-----------	--------------

additional data	signal strength excess gain operating cycles device temperature
-----------------	--

cycle time	≥ 2,7 ms
------------	----------

mechanical data

width / diameter	8 mm
------------------	------


mechanical data

height / length	25,1 mm
depth	15,8 mm
type	rectangular
mechanical mounting	threaded sleeves M3 (stainless steel)
housing material	plastic (ASA, PMMA)
front (optics)	PMMA
connection types	flylead connector M8 4 pin, L=200 mm
cable characteristics	PVC / PVC 4 x 0,08 mm ²


ambient conditions

operating temperature	-20 ... +50 °C
protection class	IP 67

dimension drawing



connection diagram




laser warning


**CLASS 1 LASER
PRODUCT**

IEC 60825-1/2014
Complies with 21 CFR 1040.10 and 1040.11
except for deviations pursuant to laser
notice No. 50, dated June 24, 2007

pin assignment



beam characteristic (typically)



excess gain curve

