

U300.D50-DP1B.72N

Article number: 11219502

overview

- Best measuring performance due to precise measuring principle
- Simple teach-in via qTeach or line teach
- Shortest blind zone in its class
- High performance in compact housing



Picture similar



Technical data

general data

scanning range Sd	15 ... 500 mm
scanning range close limit Sdc	15 ... 500 mm
scanning range far limit Sde	15 ... 500 mm
repeat accuracy	< 0,5 mm
resolution	< 0,3 mm
response time ton	< 40 ms
release time toff	< 40 ms
temperature drift	< 2 % of distance to target So
power-up drift	compensated after 15 min.
sonic frequency	290 kHz
adjustment	qTeach, line-Teach
alignment aid	light indicator flashing
light indicator	LED yellow
power on indication	LED green
alignment measuring axis	< 2°

electrical data

voltage supply range +Vs	12 ... 30 VDC
--------------------------	---------------

electrical data

current consumption typ.	35 mA
output circuit	voltage output
output signal	0 ... 10 V / 10 ... 0 V
residual ripple	< 10 % Vs
short circuit protection	yes
reverse polarity protection	yes, Vs to GND


mechanical data

type	rectangular
housing material	plastic (ASA, PMMA)
width / diameter	12,9 mm
height / length	32,2 mm
depth	23 mm
connection types	connector M8 4 pin


ambient conditions

operating temperature	-25 ... +65 °C
storage temperature	-40 ... +75 °C
protection class	IP 67


dimension drawing



connection diagram



pin assignment



typical sonic cone profile

