G3VM-21BR/ER

MOS FET Relays

DIP

G3VM-21BR/ER

Higher power, 4-A switching with a 20-V load voltage, DIP package. Low 20 mΩ ON Resistance.

- Continuous load current of 4 A. (Connection C: 8 A)
- Switches minute analog signals.
- Dielectric strength of 2,500 Vrms between I/O.



NEW

Note: The actual product is marked differently from the image shown here.

RoHS compliant

■ Application Examples

- Communication equipment
- Test & Measurement equipment
- Security equipment
- Factory Automation equipment
- Power circuit

■ Terminal Arrangement/Internal Connections



Note: The actual product is marked differently from the image shown here.

■ List of Models

Package type	Contact form	Terminals	Load voltage (peak value) ✻	Model	Minimum package quantity	
					Number per stick	Number per tape and reel
DIP6	1a (SPST-NO)	PCB terminals	20 V	G3VM-21BR	50	---
		Surface-mounting terminals		G3VM-21ER		
				G3VM-21ER (TR)	---	1,500

✻ The AC peak and DC value are given for the load voltage.

■ Absolute Maximum Ratings (Ta = 25°C)

Item			Symbol	Rating	Unit	Measurement conditions
Input	LED forward current		I_F	30	mA	
	Repetitive peak LED forward current		I_{FP}	1	A	100 μs pulses, 100 pps
	LED forward current reduction rate		ΔI_F/°C	–0.3	mA/°C	Ta ≥ 25°C
	LED reverse voltage		V_R	5	V	
	Connection temperature		T_J	125	°C	
Output	Load voltage (AC peak/DC)		V_{OFF}	20	V	
	Continuous load current	Connection A	I_O	4	A	Connection A: AC peak/DC Connection B and C: DC
		Connection B		4		
		Connection C		8		
	ON current reduction rate	Connection A	ΔI_O/°C	–40	mA/°C	Ta ≥ 25°C
		Connection B		–40		
		Connection C		–80		
	Pulse ON current		Iop	12	A	t = 100 ms, Duty = 1/10
	Connection temperature		T_J	125	°C	
Dielectric strength between I/O (See note 1.)			V_{I-O}	2500	Vrms	AC for 1 min
Operating temperature			Ta	–40 to +85	°C	With no icing or condensation
Storage temperature			Tstg	–55 to +125	°C	With no icing or condensation
Soldering temperature			---	260	°C	10 s

Note: 1. The dielectric strength between the input and output was checked by applying voltage between all pins as a group on the LED side and all pins as a group on the light-receiving side.

Connection Diagram

Connection A	
Connection B	
Connection C	

■ Electrical Characteristics (Ta = 25°C)

Item			Symbol	Minimum	Typical	Maximum	Unit	Measurement conditions
Input	LED forward voltage		V_F	1.18	1.33	1.48	V	I_F = 10 mA
	Reverse current		I_R	---	---	10	μA	V_R = 5 V
	Capacity between terminals		C_T	---	70	---	pF	V = 0, f = 1 MHz
	Trigger LED forward current		I_{FT}	---	0.5	3	mA	I_O = 1 A
Output	Maximum resistance with output ON	Connection A	R_{ON}	---	20	50	mΩ	I_F = 5 mA, I_O = 2 A, t < 1s
		Connection B		---	10	---	mΩ	I_F = 5 mA, I_O = 2 A, t < 1s
		Connection C		---	5	---	mΩ	I_F = 5 mA, I_O = 4 A, t < 1s
	Current leakage when the relay is open		I_{LEAK}	---	---	1.0	μA	V_{OFF} = 20 V
	Capacity between terminals		C_{OFF}	---	1000	---	pF	V = 0, f = 1 MHz
Capacity between I/O terminals			C_{I-O}	---	0.8	---	pF	f = 1 MHz, V_S = 0 V
Insulation resistance between I/O terminals			R_{I-O}	1000	---	---	MΩ	V_{I-O} = 500 VDC, RoH ≤ 60%
Turn-ON time			t_{ON}	---	2.5	5	ms	I_F = 5 mA, R_L = 200 Ω, V_{DD} = 20 V (See note 2.)
Turn-OFF time			t_{OFF}	---	0.1	1	ms	

Note: 2. Turn-ON and Turn-OFF Times



ПРОМЭЛЕКТРОНИКА / sales@prom-elec.com

■Recommended Operating Conditions

Use the G3VM under the following conditions so that the Relay will operate properly.

Item	Symbol	Minimum	Typical	Maximum	Unit
Load voltage (AC peak/DC)	V_{DD}	---	---	16	V
Operating LED forward current	I_F	5	10	25	mA
Continuous load current (AC peak/DC)	I_O	---	---	4	A
Operating temperature	Ta	–20	---	65	°C

■Engineering Data

LED forward current vs. Ambient temperature



Continuous load current vs. Ambient temperature



LED forward current vs. LED forward voltage



Continuous load current vs. On-state voltage



On-state resistance vs. Ambient temperature



Trigger LED forward current vs. Ambient temperature



Turn ON, Turn OFF time vs. LED forward current



Turn ON, Turn OFF time vs. Ambient temperature



Current leakage vs. Ambient temperature



■Safety Precautions

- Refer to **"Common Precautions"** for all G3VM models.

Appearance/Dimensions DIP6

■ Appearance

DIP (Dual Inline Package)

DIP6



Note: The actual product is marked differently from the image shown here.

■ Dimensions

(Unit: mm)



PCB Terminals

Weight: 0.4 g



Note: The actual product is marked differently from the image shown here.



Surface-mounting Terminals

Weight: 0.4 g



PCB Dimensions (Bottom View)



Actual Mounting Pad Dimensions

(Recommended Value, Top View)



- Application examples provided in this document are for reference only. In actual applications, confirm equipment functions and safety before using the product.
- Consult your OMRON representative before using the product under conditions which are not described in the manual or applying the product to nuclear control systems, railroad systems, aviation systems, vehicles, combustion systems, medical equipment, amusement machines, safety equipment, and other systems or equipment that may have a serious influence on lives and property if used improperly. Make sure that the ratings and performance characteristics of the product provide a margin of safety for the system or equipment, and be sure to provide the system or equipment with double safety mechanisms.

Note: Do not use this document to operate the Unit.

OMRON Corporation

ELECTRONIC AND MECHANICAL COMPONENTS COMPANY **Contact: www.omron.com/ecb**

Cat. No. K136-E1-02

0412(0412)(O)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Omron:

G3VM-21BR G3VM-21ER G3VM-21ER(TR)