




Recommended LED forward current 2 mA, High Sensitivity (Low current-consumption) Miniature SOP4-pin Type

PhotoMOS[®] HS SOP 1 Form A (AQY230S)



FEATURES

1. High sensitivity (Low current-consumption)
HS type PhotoMOS need less than half LED forward current of other types. This contributes to energy-saving working of equipment and longer operating life for battery.

Sensitivity comparison between HS type and GU type			
In case of load voltage 60V type, SOP4-pin			
LED operate current	Typical	HS type (AQY232S)	GU type (AQY212S)
	Maximum	0.35 mA	0.9 mA
Recommended LED forward current		2 mA	5 mA

2. Small package (SOP4-pin)
3. 60 V, 350 V and 400 V load voltage types available

TYPICAL APPLICATIONS

Ideal for battery-powered devices that need to lengthen operating life.
Also recommended for power-economizing of testing equipment that uses many relays.

- 1. Security equipment**
 - Crime-preventing system: Surveillance camera, burglar alarm
 - Disaster-preventing system: Fire alarm, heat/smoke sensor
- 2. Measuring instruments**
- 3. Meters (watt-hour, gas, etc.)**
- 4. Telecommunication equipment**
- 5. Industrial equipment**
- 6. Battery operating equipment**

TYPES

	Output rating*		Package	Part No.			Packing quantity	
	Load voltage	Load current		Tube packing style	Tape and reel packing style		Tube	Tape and reel
					Picked from the 1/2-pin side	Picked from the 3/4-pin side		
AC/DC dual use	60V	500mA	SOP4-pin	AQY232S	AQY232SX	AQY232SZ	1 tube contains: 100 pcs.	1,000 pcs.
	350V	120mA		AQY230S	AQY230SX	AQY230SZ	1 batch contains: 2,000 pcs.	
	400V	100mA		AQY234S	AQY234SX	AQY234SZ		

Note: For space reasons, the three initial letters of the part number “AQY”, the surface mount terminal indicator “S” and the packing style indicator “X” or “Z” are not marked on the device. (Ex. the label for product number AQY232SX is 232.)
* Indicate the peak AC and DC values.

Ratings and packages other than those given above are available by special order. Please contact our sales office in your area.

RATING


1. Absolute maximum ratings (Ambient temperature: 25°C 77°F)

Item		Symbol	AQY232S	AQY230S	AQY234S	Remarks
Input	LED forward current	I _F	50 mA			
	LED reverse voltage	V _R	5 V			
	Peak forward current	I _{FP}	1 A			f = 100 Hz, Duty factor = 0.1%
	Power dissipation	P _{in}	75 mW			
Output	Load voltage (peak AC)	V _L	60 V	350 V	400 V	
	Continuous load current	I _L	0.5 A	0.12 A	0.1 A	Peak AC, DC
	Peak load current	I _{peak}	1.5 A	0.3 A	0.24 A	100ms (1 shot), V _L = DC
	Power dissipation	P _{out}	300 mW			
Total power dissipation		P _T	350 mW			
I/O isolation voltage		V _{iso}	1,500 Vrms			
Ambient temperature	Operating	T _{opr}	-40 to +85°C -40 to +185°F			(Non-icing at low temperatures)
	Storage	T _{stg}	-40 to +100°C -40 to +212°F			

2. Electrical characteristics (Ambient temperature: 25°C 77°F)

Item			Symbol	AQY232S	AQY230S	AQY234S	Condition
Input	LED operate current	Typical	I _{Fon}	0.35 mA			ΔI _F /Δt ≥ 100 μA/s I _L = Max.
		Maximum		0.5 mA			
	LED turn off current	Minimum	I _{Foff}	0.1 mA			ΔI _F /Δt ≥ 100 μA/s I _L = Max.
		Typical		0.3 mA			
	LED dropout voltage	Typical	V _F	1.25 V (1.1 V at I _F = 2 mA)			I _F = 50 mA
		Maximum		1.5 V			
Output	On resistance	Typical	R _{on}	0.85 Ω	19 Ω	27 Ω	I _F = 2 mA I _L = Max. Within 1 s
		Maximum		2.5 Ω	25 Ω	35 Ω	
	Off state leakage current	Maximum	I _{Leak}	1 μA			I _F = 0 mA V _L = Max.
	Transfer characteristics	Turn on time*	Typical	T _{on}	1.5 ms	1.2 ms	0.8 ms
Maximum			5 ms				
Turn off time*		Typical	T _{off}	0.15 ms	0.1 ms	0.1 ms	I _F = 2 mA I _L = Max.
		Maximum		2 ms			
I/O capacitance		Typical	C _{iso}	0.8 pF			f = 1 MHz V _B = 0 V
		Maximum		1.5 pF			
Initial I/O isolation resistance	Minimum	R _{iso}	1,000 MΩ			500 V DC	

*Turn on/Turn off time



3. Recommended operating conditions (Ambient temperature: 25°C 77°F)

Please use under recommended operating conditions to obtain expected characteristics.


Item		Symbol	Min.	Max.	Unit
LED current		I _F	2	30	mA
AQY232S	Load voltage (Peak AC)	V _L	—	48	V
	Continuous load current	I _L	—	0.5	A
AQY230S	Load voltage (Peak AC)	V _L	—	280	V
	Continuous load current	I _L	—	0.12	A
AQY234S	Load voltage (Peak AC)	V _L	—	320	V
	Continuous load current	I _L	—	0.1	A

■ These products are not designed for automotive use.
If you are considering to use these products for automotive applications, please contact your local Panasonic Corporation technical representative.

REFERENCE DATA


1. Load current vs. ambient temperature characteristics

Allowable ambient temperature: -40 to +85°C
-40 to +185°F




2. On resistance vs. ambient temperature characteristics

Measured portion: between terminals 3 and 4;
LED current: 2 mA; Load voltage: Max. (DC);
Continuous load current: Max. (DC)




3. Turn on time vs. ambient temperature characteristics

LED current: 2 mA; Load voltage: Max. (DC);
Continuous load current: Max. (DC)




4. Turn off time vs. ambient temperature characteristics

LED current: 2 mA; Load voltage: Max. (DC); Continuous load current: Max. (DC)




5. LED operate current vs. ambient temperature characteristics

Sample: All types; Load voltage: Max. (DC); Continuous load current: Max. (DC)




6. LED turn off current vs. ambient temperature characteristics

Sample: All types; Load voltage: Max. (DC); Continuous load current: Max. (DC)




7. LED dropout voltage vs. ambient temperature characteristics

Sample: All types; LED current: 2 to 50 mA




8-(1). Current vs. voltage characteristics of output at MOS portion

Measured portion: between terminals 3 and 4; Ambient temperature: 25°C 77°F




8-(2). Current vs. voltage characteristics of output at MOS portion

Measured portion: between terminals 3 and 4; Ambient temperature: 25°C 77°F




9. Off state leakage current vs. load voltage characteristics

Measured portion: between terminals 3 and 4; Ambient temperature: 25°C 77°F




10. Turn on time vs. LED forward current characteristics

Measured portion: between terminals 3 and 4; Load voltage: Max. (DC); Continuous load current: Max. (DC); Ambient temperature: 25°C 77°F




11. Turn off time vs. LED forward current characteristics

Measured portion: between terminals 3 and 4; Load voltage: Max. (DC); Continuous load current: Max. (DC); Ambient temperature: 25°C 77°F



12. Output capacitance vs. applied voltage characteristics

Measured portion: between terminals 3 and 4; Frequency: 1 MHz (30 mVrms); Ambient temperature: 25°C 77°F



"PhotoMOS®", "PhotoMOS" and "PHOTOMOS" are registered trademarks of Panasonic Corporation.

*Recognized in Japan, the United States, all member states of European Union and other countries.

Please contact

Panasonic Corporation

Electromechanical Control Business Division

■ 1006, Oaza Kadoma, Kadoma-shi, Osaka 571-8506, Japan
industrial.panasonic.com/ac/e/

Panasonic®

©Panasonic Corporation 2017

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panasonic:

[AQY230S](#) [AQY230SX](#) [AQY230SZ](#) [AQY234S](#) [AQY234SX](#) [AQY234SZ](#) [AQY232S](#) [AQY232SX](#) [AQY232SZ](#)