
E33602

Process adapter Tri-Clamp

ADAPT G1-CLAMP ISO2852/1-1.5



1: Leakage port

EC 1935/2004 FCM FCM JP FDA

Application			
Design	with leakage port		
Pressure rating	100 bar	10 MPa	
Tests / approvals			
Pressure Equipment Directive	A possible classification to PED depends on the application and has to be carried out by the user / operator.		
Safety instructions	The compatibility between medium and product material has to be checked in all applications.		
Mechanical data			
Weight [g]	156.5		
Materials (wetted parts)	stainless steel (316L/1.4435) surface characteristics: Ra < 0,4 µm / Rz = 4 µm		
Sensor connection	G 1 sealing cone - 27 mm		
Process connection	Clamp DN25...DN40 (1...1,5") DIN 32676 (ISO 2852)		
Suitable for process connections in accordance with the standards	DIN 32676 series A (DIN)	clamp DN32, DN40	
	DIN 32676 series B (ISO)	clamp DN33,7	
	DIN 32676 series C (ASME BPE)	clamp 1,5"	
	ISO 2852	clamp DN33,7, DN38	
Sealing	Gasket		
Hygienic equipment class to DIN 11866	H4		
Accessories			
Items supplied	O-rings: 1 x (26 x 3 mm), EPDM, FDA compliant, E30438		
	O-rings: 1 x (26 x 3 mm), FKM, FDA compliant, E30437		

E33602

Process adapter Tri-Clamp

ADAPT G1-CLAMP ISO2852/1-1.5

Remarks	
Pack quantity	1 pcs.