
KT5151

Illuminated capacitive touch sensor

KTMBF-KRGBPKG/US/0,3M

Article no longer available - archive entry

Alternative articles: KTE101 or KTE102
When selecting an alternative article and accessories please note that technical data may differ!



Product characteristics		
Electrical design		PNP
Output function		normally open
Housing		threaded type
Dimensions	[mm]	M22 x 1.5 / L = 31
Application		
Operating principle		bistable
Electrical data		
Operating voltage	[V]	12...30 DC
Current consumption	[mA]	30
Protection class		III
Reverse polarity protection		yes
Max. power-on delay time	[ms]	500
Outputs		
Electrical design		PNP
Output function		normally open
Permanent current rating of switching output DC	[mA]	200
Short-circuit protection		yes
Overload protection		yes
Response times		
Response time	[ms]	35
Operating conditions		
Ambient temperature	[°C]	-40...85
Protection		IP 65; IP 67; IP 69K; (on the front)

KT5151

Illuminated capacitive touch sensor

KTMBF-KRGBPKG/US/0,3M

Mechanical data		
Weight	[g]	55
Housing		threaded type
Dimensions	[mm]	M22 x 1.5 / L = 31
Thread designation		M22 x 1.5
Materials		PA 6.6; active face: PA Grilamid TR 90UV

Displays / operating elements		
Display	switching status	1 x LED, green
	function	1 x LED, red can be triggered

Accessories	
Items supplied	lock nuts: 1 x M22
	Gasket: 1
Accessories (optional)	symbol disc

Remarks	
Pack quantity	1 pcs.

Electrical connection - plug

Cable: 0.3 m, PUR

Connector: 1 x M12; coding: A; Contacts: 4



Connection

