



EH-422

Sensor Head, Unshielded Type, f22



*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.


Specifications

Model		EH-422
Type		Standard , Non-shielded , Cylindrical and threaded
Detectable object		Ferrous metals (see Characteristics for nonferrous metals)
Standard target (iron, t=1 mm 0.04")		25 x 25 mm 0.98" x 0.98"
Stable detecting range		0 to 9 mm0.35"
Maximum detecting distance		18 mm0.71"
Hysteresis		0.06 mm0.002"
Repeatability		0.02 mm0.0008"
Temperature characteristics		±10% max. of detecting distance at 23°C 73.4°F, within -10 to +60°C 14 to 140°F
Environmental resistance	Enclosure rating	IP67
	Ambient temperature	-10 to +60 °C 14 to 140 °F (No freezing)
	Relative humidity	35 to 85 % RH (No condensation)
Weight		Approx. 175 g (including nuts and 3-m 9.8' cable)

Dimensions

* Download CAD file or product manual for larger image/text and more detail.


EH-422



Characteristic

* Download CAD file or product manual for larger image/text and more detail.

Long-distance Separate-amplifier Proximity Sensors



Long-distance Separate-amplifier Proximity Sensors

