



GV-H450

Sensor Head Long-distance Type



*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

Specifications

Model			GV-H450
Type			Long-range
Light source			Visible semiconductor laser, Wavelength: 655 nm
Laser class	FDA (CDRH) Part 1040.10		Class 2 (560 μW)
	IEC 60825-1		
	JIS C6802		
Detection distance (Amplifier display)			160 to 450 mm 6.30" to 17.72" (290 to 0)*1)
Possible display range			295 to -50
Standard detection deviation			3 mm 0.12"
Spot diameter			Approx. ø0.8 mm ø0.031" (Detection distance 450 mm 17.72")
Operation status indicators			Control output: Red LED/Laser radiation emission indicator: Green LED/1 spot indicator: Green LED
Environmental resistance	Enclosure rating		IP67
	Operating ambientluminance	Incandescent lamp	5000lx
		Sunlight	10000lx
	Ambient temperature		-10 to +50 °C 14 to 122 °F (No freezing)
	Relative humidity		35 to 85 % RH (No condensation)
	Vibration resistance		10 to 55 Hz, Double amplitude 1.5 mm 0.06", 2 hours in each of the X, Y, and Z axis
Material			Housing material: PBT, Display: Polyarylate, Metal: SUS304, Lens cover: Glass, Cable: PVC
Weight			Approx. 190 g*2

*1 General guideline for amplifier display values relative to detection distance (when distance display mode is set to normal).

*2 Including 2 m 6.6' connector cable (3 m 9.8' cable for GV-H1000)

Dimensions

* Download CAD file or product manual for larger image/text and more detail.

