



NQ-EP4L

4-Port EtherNet/IP™ compatible IO-Link Master Module



*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

Specifications

Model		NQ-EP4L
Network Specifications	Compatible Networks	EtherNet/IP™, Modbus/TCP
	Communication Speed	10 Mbps/100 Mbps
	Connector	M8 4-pin female A-code
Power Supply Specifications	Connector Type	Power supply port IN: M8 4-pin male A-code Power supply port OUT: M8 4-pin female A-code
	Power Voltage	18 to 30 VDC (During IO-Link communication: 20.4 V to 28.8 V)
	Allowable Current	V1 and V2: max. 4 A each
	Current Consumption	V1: max. 110 mA V2: max. 115 mA
Sensor Connection Specifications	Connector Type	M12 5-pin female A-code
	V1 Power Supply Capacity	-
	V2 Power Supply Capacity	Ports 1 to 4: 4 A in total
IO-Link Specifications	Number of Connectable Devices	4
	Compliant Standards	Ver1.1
	Transmission Speed	COM1: 4.8 kbps COM2: 38.4 kbps COM3: 230.4 kbps
	Port type	Ports 1 to 4: Class A*1
	Process Data Size	Input: Max. 32 bytes/Output: Max. 32 bytes
Digital Input (DI) Specifications	Number of Inputs	Max. 8 (when using DI mode)
	Input Type	PNP
	ON Voltage/ON Current	11 V or higher/2 mA or higher
	OFF Voltage/OFF Current	Less than 5 V/less than 1.5 mA
	Input Current	Pin 2: approx. 7 mA, Pin 4: approx. 12 mA
Digital Output (DO) Specifications	Number of Outputs	Max. 4
	Output Type	PNP
	Maximum Load Current	Each port max. 0.5 A
	Short-Circuit Protection Circuit	Yes
	Leakage Current	0.1 mA or lower
	Residual Voltage	1 V or lower
Environmental resistance	Enclosure rating	IP65/IP67/IP69K
	Ambient temperature	-40°C to +70°C -40°F to +158°F (no freezing)
	Vibration resistance	5 to 150 Hz/20 G/10 sweeps each in X, Y, and Z axes
	Shock resistance	15 G/11 ms/3 times each in X, Y, and Z axes
Case Material		Housing: PA6-GF30

	Connector: SUS303
Weight	Approx. 190 g

*1 When using Class B, V1 and V2 each require a power supply.

* Download CAD file or product manual for larger image/text and more detail.

