



PZ-G41EN

Square Reflective M12 Connector Type with Cable, NPN



*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

Specifications

Model		PZ-G41EN
Type		Diffuse Reflective, Long-range
Shape		Rectangular
Output		NPN
Cable connection		M12 pigtail connector *1
Detecting distance		1 m 3.3' (When detecting 30 x 30 cm 11.81"x11.81" white paper)
Spot diameter		—
Light source		Red LED
Sensitivity adjustment		1-turn trimmer (230°)
Response time		500 μs
Operation mode		LIGHT-ON/DARK-ON (switch-selectable)
Indicators (LED)		Output: Orange LED, Stable operation: Green LED
Control output		Open collector output, 30 V max., 100 mA max., Residual voltage: 1 V max.
Protection circuit		Reversed polarity, overcurrent protection, surge absorber
Interference suppression		Up to 2 units (with the automatic different frequency function)
Tightening torque		Rectangular models (Mounting hole part): 0.5 N m max.
Rating	Power voltage	10 to 30 VDC, including Ripple (P-P) 10 %
	Current consumption	34 mA or less
Environmental resistance	Enclosure rating	IEC: IP67/NEMA: 4A, 6, 12/DIN: IP69K
	Ambient light	Incandescent lamp: 5,000 lux max., Sunlight: 20,000 lux max.
	Ambient temperature	-20 to +55 °C -4 to 131 °F (No freezing)
	Relative humidity	35 to 85 % RH (No condensation)
	Vibration resistance	10 to 55 Hz, Double amplitude 1.5 mm 0.06", 2 hours in each of the X, Y, and Z directions
	Shock resistance	1,000 m/s ² , 6 times in each of the X, Y, and Z directions
Material	Housing, M18 nut (threaded models only)	Glass-fiber reinforced PBT
	Lens cover	Polyarylate (PAR)
	Trimmer	Glass-fiber reinforced polyamide (PA)
	Case connection	Screw: Nickel-plated iron and zinc, packing: nitrile butadiene rubber (NBR)
	Cable (cable models only)	Polyvinyl chloride (PVC)


Accessories	Instruction manual
Weight	Rectangular M12 pigtail quick disconnect model: Approx. 30 g

*1 Cable sold separately for connector models


Dimensions

* Download CAD file or product manual for larger image/text and more detail.

PZ-G41EN/G41EP/G42EN/G42EP



Detail of cable + connector




Pin arrangement

1	+V
2	-
3	OV
4	OUT

I/O Circuit Connection diagram

* Download CAD file or product manual for larger image/text and more detail.

NPN output
(thru-beam receiver, reflective, retro-reflective)



Characteristic

* Download CAD file or product manual for larger image/label and more detail.

