



PZ-G42B

Threaded mount Reflective Cable Type, NPN



*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

Specifications

Model		PZ-G42B
Type		Diffuse Reflective Short-range
Shape		Threaded
Output		Bipolar (NPN+PNP)
Cable connection		Cable (2 m 78.74") *1
Detecting distance		300 mm 11.81" (When detecting 10 x 10 cm 3.94" x 3.94" white paper)
Spot diameter		—
Light source		Red LED
Sensitivity adjustment		1-turn trimmer (230°)
Response time		500 μs
Operation mode		LIGHT-ON/DARK-ON (switch-selectable)
Indicators (LED)		Output: Orange LED, Stable operation: Green LED
Control output		Open collector output, 30 V max., 100 mA max., Residual voltage: 1 V max.
Protection circuit		Reversed polarity, overcurrent protection, surge absorber
Interference suppression		Up to 2 units (with the automatic different frequency function)
Tightening torque		Threaded models (front M18 part): 1.0 N m max., (side slotted hole part): 0.5 N m max.
Rating	Power voltage	10 to 30 VDC, including Ripple (P-P) 10 %
	Current consumption	34 mA or less
Environmental resistance	Enclosure rating	IEC: IP67/NEMA: 4A, 6, 12/DIN: IP69K
	Ambient light	Incandescent lamp: 5,000 lux max., Sunlight: 20,000 lux max.
	Ambient temperature	-20 to +55 °C -4 to 131 °F (No freezing)
	Relative humidity	35 to 85 % RH (No condensation)
	Vibration resistance	10 to 55 Hz, Double amplitude 1.5 mm 0.06", 2 hours in each of the X, Y, and Z directions
	Shock resistance	1,000 m/s ² , 6 times in each of the X, Y, and Z directions
Material	Housing, M18 nut (threaded models only)	Glass-fiber reinforced PBT
	Lens cover	Polyarylate (PAR)
	Trimmer	Glass-fiber reinforced polyamide (PA)


	Case connection	Screw: Nickel-plated iron and zinc, packing: nitrile butadiene rubber (NBR)
	Cable (cable models only)	Polyvinyl chloride (PVC)
	Connector (connector type with cable only)	—
Accessories		Instruction manual, M18 nut x 1 piece (threaded models only)
Weight		Threaded cable models: Approx. 65 g (Thrubeam-models transmitter: Approx. 55 g)

*1 Cable sold separately for connector models

Dimensions

* Download CAD file or product manual for larger image/text and more detail.


PZ-G41B/G42B



I/O Circuit Connection diagram

* Download CAD file or product manual for larger image/text and more detail.

Bipolar output
(thru-beam receiver, reflective, retro-reflective)



Characteristic

* Download CAD file or product manual for larger image/target and more detail.

