



PZ-G52CP

Square Transmissive M8 Connector Type, PNP



*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

Specifications

Model		PZ-G52CP
Type		Thrubeam, High-power
Shape		Rectangular
Output		PNP
Cable connection		M8 connector *1
Detecting distance		40 m (131.2')
Spot diameter		—
Light source		Infrared LED x 2
Sensitivity adjustment		1-turn trimmer (230°)
Response time		500 μs
Operation mode		LIGHT-ON/DARK-ON (switch-selectable)
Indicators (LED)		Power (T): Orange LED Output (R): Orange LED Stable operation: Green LED Light receiving: Red LED
Control output		Open collector output, 30 V max., 100 mA max., Residual voltage: 1 V max.
Protection circuit		Reversed polarity, overcurrent protection, surge absorber
Interference suppression		Up to 2 units (When polarization filters are attached)
Tightening torque		Rectangular models (Mounting hole part): 0.5 N m max.
Rating	Power voltage	10 to 30 VDC, including Ripple (P-P) 10 %
	Current consumption	Transmitter: 25 mA or less, Receiver: 28 mA or less
Environmental resistance	Enclosure rating	IEC: IP67/NEMA: 4A, 6, 12/DIN: IP69K
	Ambient light	Incandescent lamp: 5,000 lux max., Sunlight: 20,000 lux max.
	Ambient temperature	-20 to +55 °C -4 to 131 °F (No freezing)
	Relative humidity	35 to 85 % RH (No condensation)
	Vibration resistance	10 to 55 Hz, Double amplitude 1.5 mm 0.06", 2 hours in each of the X, Y, and Z directions
	Shock resistance	1,000 m/s ² , 6 times in each of the X, Y, and Z directions
Material	Housing, M18 nut (threaded models only)	Glass-fiber reinforced PBT
	Lens cover	Polyarylate (PAR)
	Trimmer	Glass-fiber reinforced polyamide (PA)
	Case connection	Screw: Nickel-plated iron and zinc, packing: nitrile butadiene rubber (NBR)
	Cable (cable models only)	Polyvinyl chloride (PVC)

	Connector (connector type with cable only)	—
Accessories		Instruction manual
Weight		Rectangular connector models: Approx. 10 g


*1 Cable sold separately for connector models

Dimensions

* Download CAD file or product manual for larger image/text and more detail.

PZ-G52CN/G52CP


Receiver



Pin arrangement

①	+V
②	-
③	0V
④	OUT

Transmitter




Pin arrangement

①	+V
②	-
③	0V
④	-


I/O Circuit Connection diagram

* Download CAD file or product manual for larger image/text and more detail.

Thrubeam transmitter



PNP output (thrubeam receiver, reflective, retro-reflective)



Characteristic

* Download CAD file or product manual for larger image/text and more detail.

