

EU type examination certificate

EU-Baumusterprüfbescheinigung

CE-0085BR0233

Product Identification No.
Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EU Gas Appliances Regulation (EU/2016/426) <i>EU-Gasgeräteverordnung (EU/2016/426)</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Elster GmbH Strotheweg 1, D-49504 Lotte (Büren)
Distributor <i>Vertreiber</i>	Elster GmbH Strotheweg 1, D-49504 Lotte (Büren)
Product Category <i>Produktart</i>	gas fittings: Valve combined with thermically triggered shut-off device (4341)
Product Description <i>Produktbezeichnung</i>	ball valve in pass-through form, input side with integrated thermically triggered shut-off device (TAE) to protect behind installed objects
Model <i>Modell</i>	AKT...R10TAS
Countries of Destination <i>Bestimmungsländer</i>	AT, BE, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MT, NL, NO, PL, PT, SE, SI, SK
Test Reports <i>Prüfberichte</i>	type testing: 17/348/4341/123 from 18.01.2018 (EBI)
Test Basis <i>Prüfgrundlagen</i>	EU/2016/426 A III B (09.03.2016) DIN EN 331 (01.04.2016) DIN 3586 (01.10.2003)

Validity / File no. 21.04.2018 until 26.02.2028 / 17-0962-GEA
Gültigkeit / AZ

26.02.2018 Rie A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of gas appliances under EU Regulation

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Gasgeräten gemäß EU-Verordnung EU/2016/426.



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-01

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Gas Category <i>Gasart</i>	Remarks <i>Bemerkungen</i>
fuel gases of the 1., 2. & 3. gas family	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
AKT 15 R10TAS	pressure class: MOP 5 / C 1 nominal diameter: DN 15	
AKT 20 R10TAS	pressure class: MOP 5 / C 1 nominal diameter: DN 20	
AKT 25 R10TAS	pressure class: MOP 5 / C 1 nominal diameter: DN 25	

Hints of Utilization /Remarks**Verwendungshinweise / Bemerkungen**

type of connecting: at both sides internal thread Rp 1/2 up to Rp 1 according to DIN EN 10226-1
 ambient temperature range: -20...+60 °C
 temperature of releasing: +95 °C (± 5 K)
 thermal resistance: +650 °C up to pressures of 1 bar (class: C 1)