



Number:	UKCA/0558/22/053	Replaces:	17GR0205/00
Issue Date:	04-02-2022	Contract Number:	PS7133
Due Date:	04-02-2032	Module:	B (Type Testing)
Report Number:	120408	Scope:	Gas Appliances
PIN:	0063AU1408	Page	1 of 2

UKCA TYPE EXAMINATION CERTIFICATE

Kiwa Ltd. hereby declares that the model type(s)

GFK...

Manufactured by Elster GmbH (Honeywell)
Lotte - Büren, Germany

Meet(s) the essential requirements as described in the:

Gas Appliances Regulation (Regulation (EU) 2016/426 as brought into GB law and amended), and the Gas Appliances (Enforcement) and Miscellaneous Amendment Regulations 2018 No 389, and amendments to UK SI 2019/696 Product Safety and Metrology, and subsequent amendments, The Product Safety, Metrology and Mutual Recognition Agreement (Amendment) (EU Exit) Regulations 2019 No 1246, and subsequent amendments. This certificate is not valid in Northern Ireland – and is applicable to England, Scotland and Wales only.

Reference standards: BS EN 13611:2007+A2:2011

Signed on behalf of Kiwa Ltd.
(UK Approved Body Number 0558)

Mark Crowther
Technical Director
Kiwa Ltd.

390/170501

CERTIFICATE

Kiwa Gastec
Kiwa House
Malvern View Business Park
Stella Way
Bishops Cleeve
Cheltenham
GL52 7DQ
United Kingdom
T +44 (0)1242 677877
F +44 (0)1242 676506
www.kiwa.co.uk



0217



Number:	UKCA/0558/22/053	Replaces:	17GR0205/00
Issue Date:	04-02-2022	Contract Number:	PS7133
Due Date:	04-02-2032	Module:	B (Type Testing)
Report Number:	120408	Scope:	Gas Appliances
PIN:	0063AU1408	Page	2 of 2

APPENDIX TO UKCA TYPE EXAMINATION CERTIFICATE

List of all available types:

Gas filter approved on relevant clauses of EN 13611.

Type Number Survey:

GFK	Gas Filter
15	Connection size 15
20	Connection size 20
25	Connection size 25
32	Connection size 32
40	Connection size 40
50	Connection size 50
65	Connection size 65
80	Connection size 80
100	Connection size 100
125	Connection size 125
150	Connection size 150
200	Connection size 200
250	Connection size 250
R	Rp thread (connection size 15, 20, 25, 32, 40, 50, 65)
F	DIN flanged (connection size 40, 50, 65, 80, 100, 125, 150, 200, 250)
N	NPT thread (connection size 15, 20, 25, 32, 40, 50, 65)
A	ANSI flanged (connection size 40, 50, 65, 80, 100)
T	T product
10	pe max. = 1 bar
40	pe max. = 4 bar
60	pe max. = 6 bar
-3	Plug screw at the inlet and outlet
-6	Measuring adapter at the inlet and outlet

Special conditions:

None