



Number:	UKCA/0558/21/304	Replaces:	17GR0207/00
Issue Date:	06-12-2021	Contract Number:	PS7133
Due Date:	06-12-2031	Module:	B (Type Testing)
Report Number:	119418	Scope:	Gas Appliances
PIN:	0063BL1553	Page	1 of 2

UKCA TYPE EXAMINATION CERTIFICATE

Kiwa Ltd. hereby declares that the model type(s)

VG

Manufactured by Elster GmbH (Honeywell)
Lotte - Büren, Germany

Meet(s) the essential requirements as described in the:

Gas Appliances Regulation (Regulation (EU) 2016/426 as brought into GB law and amended), and the Gas Appliances (Enforcement) and Miscellaneous Amendment Regulations 2018 No 389, and amendments to UK SI 2019/696 Product Safety and Metrology, and subsequent amendments, The Product Safety, Metrology and Mutual Recognition Agreement (Amendment) (EU Exit) Regulations 2019 No 1246, and subsequent amendments. This certificate is not valid in Northern Ireland – and is applicable to England, Scotland and Wales only.

Reference standards: BS EN 161:2011+A3:2013

Signed on behalf of Kiwa Ltd.
(UK Approved Body Number 0558)

Mark Crowther
Technical Director
Kiwa Ltd.

390/1709/01

CERTIFICATE

Kiwa Gastec
Kiwa House
Malvern View Business Park
Stella Way
Bishops Cleeve
Cheltenham
GL52 7DQ
United Kingdom
T +44 (0)1242 677877
F +44 (0)1242 676506
www.kiwa.co.uk



0217



Number:	UKCA/0558/21/304	Replaces:	17GR0207/00
Issue Date:	06-12-2021	Contract Number:	PS7133
Due Date:	06-12-2031	Module:	B (Type Testing)
Report Number:	119418	Scope:	Gas Appliances
PIN:	0063BL1553	Page	2 of 2

APPENDIX TO UKCA TYPE EXAMINATION CERTIFICATE

List of available types:

VG: Electro-magnetic automatic shut-off valve approved on EN161
Electrical supply: 220/240 VAC, 120VAC; 24VDC
Ambient temperature range: -20°C to 60°C
IP Protection degree: IP54
Class: A
Mechanical strength: group 2
Working pressure: up to 360 mbar
Connection size: Rp internal thread DN 15, 20, 25, 32, 40 (ISO7)
DIN Flange DN 32, 40, 50, 65 (ISO7005)

Type Survey:

VG	Gas solenoid valve
10/15 - 65	Nominal diameter
R	Rp internal thread ISO7
F	Flange to ISO 7005
02	p. max. 200 mbar
03	p. max. 360 mbar
L	Slow opening, quick closing
N	Quick opening, quick closing
T	Mains voltage 220/240V AC, 50/60Hz
Q	Mains voltage 120V AC, 50/60Hz
K	Mains voltage 24 V DC
3	Terminal connection box IP54
6	Electrical connection with socket 6L
6L	Electrical connection with socket incl. lamp
1	Screw plug at the inlet
3	Screw plug at the outlet
D	With flow adjuster
M	Suitable for biologically produced methane
V	Viton valve disc seal
Z	With rolling diaphragm

F045-A v.1