

Technical data sheet

Connection cable

Part no.: 50141463

KD PL-M12-5A-P0-050

Contents

- Technical data
- Electrical connection




Figure can vary



Technical data

Basic data

Suitable for	MD 748i
--------------	---------

Electrical data

Performance data

Operating voltage	50 V AC / 60 V DC
-------------------	-------------------

Connection

Connection 1

Type of connection	Connector
--------------------	-----------

Thread size	M12
-------------	-----

Type	Male
------	------

No. of pins	5 -pin
-------------	--------

Encoding	L-coded
----------	---------

Design	Axial
--------	-------

Cable properties

Number of conductors	5 Piece(s)
----------------------	------------

Wire cross section	1.5 mm ²
--------------------	---------------------

Sheathing color	Gray
-----------------	------

Shielded	No
----------	----

Cable design	Connection cable (open on one end)
--------------	------------------------------------

Cable diameter (external)	2.35 mm
---------------------------	---------

Cable length	5,000 mm
--------------	----------

Sheathing material	PUR
--------------------	-----

Suitability for drag chains	Yes
-----------------------------	-----

Traverse rate	Max. 3.3 m/s with horiz. traverse path of 5m and and max. acceleration of 5m/s ²
---------------	---

Environmental data

Ambient temperature, operation, flexible use	-30 ... 90 °C
--	---------------

Ambient temperature, operation, stationary use	-40 ... 90 °C
--	---------------

Certifications

Degree of protection	IP 65
----------------------	-------

IP 67

IP 69K

Certifications	c UL US
----------------	---------

Classification

Customs tariff number	85444290
-----------------------	----------

eCl@ss 8.0	27279218
------------	----------

eCl@ss 9.0	27060311
------------	----------

ETIM 5.0	EC001855
----------	----------

ETIM 6.0	EC001855
----------	----------

Electrical connection

Connection 1

Type of connection	Connector
Thread size	M12
Type	Male
No. of pins	5 -pin
Encoding	L-coded
Design	Axial

Pin

1	Brown
2	White
3	Blue
4	Black
5	Gray

Conductor color

