

FG

FGRHD/DT-0A

Photo.Midi,Relay-NO+NC,Cable,E + R

COMPACT PHOTOELECTRIC SWITCH SENSORS WITH HIGH PERFORMANCES AND HIGH DETECTION DISTANCES

OVERVIEW

- Cable output or with revolving connector, NPN or PNP output (DC models) and SPDT voltage free relay output (AC models)
- Selectable LO/DO output status
- Totally protected against electrical damages
- Background suppressions models: 310 mm, 600 mm
- Reflex polarized sensitivity adjustment 12 m
- Emitter and Receiver with max detecting range of 50 m
- Double Multifunction LED indicator: output state and using the pointing
- Sensitive adjustment models

CE

TECHNICAL FEATURES

Detection properties	
Nominal sensing distance	50m
Sensitivity adjustment	Potentiometer 2 turns with position indicator (emitter)

Application	
Function Principle	Emitter and Receiver

Optic position	Axial
Emitter Code	FGRH/00-0E
Receiver Code	FGRD/0P-0E

Outputs

Output type	Relay SPDT NO+NC
Output Function	NO+NC
Switching frequency	33Hz
Response time	15,15ms

Electrical data

Operating Voltage	24...240VDC/24...240VDC/50-60Hz
No-Load supply current	≤ 35mA (emitter), ≤ 20mA (receiver)
LED indicators	Green (powerON) Yellow (status output)
Time delay before availability	≤200ms
Short-circuit protection	Yes
Reverse Polarity Protection	Yes
Emission	LED Red
Interference to external light	10,000Lux (minimum sunlight), 3,000 min HF lamp
Impulsive Overvoltage Protection	Yes

Mechanical data

Dimensions	20x44,9x60mm
Material	
Housing material	ABS
Weight	
Connections	2m PVC cable
Active Head Material	PMMA
Operating temperature	-25°C…+55°C
Diameter/Dimension	Cubic

Test/Approvals

Approvals	CE UR
EMC compatibility	EN 60947-5-2
Shocks and vibrations	Vibration IEC 60068-2-6 / Shock IEC 60068-2-28
Degree of protection	IP67

Accessories

Supplied Accessories	Mounting bracket STFG 00

Generical Data


Dimensions	20x44,9x60mm
Operating Temperature	- 25°C…+ 55°C (Without freeze)

Mechanical Protection	IP67


CONNECTIONS

Eletrical diagram

FGRH/D0




FGRD/DT



OTHERS

Dimensions



Datasensing S.r.l.
Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

date of printing
04/11/2026
11:13:41