


# PFM

## PFM1/BP-4H

**Ind.M12,PNP-NO+NC,M12 Plug,Nsch-LD**

**M12 CYLINDRICAL INDUCTIVE SENSORS FOR FOOD AND BEVERAGE APPLICATIONS**

# OVERVIEW

- AISI 316L (DIN 1.4404) stainless steel housing
- LED status indicator
- IP67 – IP68 – IP69K protection degree
- ATEX models, cat. 3, available on request
- Complete protection against electrical damages
- Standard and long distance models

# TECHNICAL FEATURES

Detection properties

| | |
|---|---|
| Nominal sensing distance | 8mm |
| Operanting distance | 0…6,48mm |
| Standard target | 24x24mm FE360 |
| Correction Factor | copper: 0,33 / aluminium: 0,40 / brass: 0,45 / stainless steel: 0,75 |
| Thermal drift of Sr | < 10% |

| | |
|---|---|
| Repeat Accuracy | < 5% (UB 24V Ta=23°C ±5°C) |
| Hysteresis | 1 … 20% |

Application

| | |
|---|---|
| Description | M12 standard no-flush mount |
| Functions | Proximity |

Outputs

| | |
|---|---|
| Output type | PNP |
| Output Function | NO + NC |
| Switching frequency | 2kHz |

Electrical data

| | |
|---|---|
| Operating Voltage | 10...30Vdc |
| No-Load supply current | ≤ 15mA |
| Load current | ≤ 200mA |
| Leakage current | ≤ 15μA |
| Output voltage drop | ≤ 2V @200mA |
| Max ripple content | ≤ 10% |
| LED indicators | Yellow LED output state |
| Time delay before availability | ≤ 50ms |

| | |
|---|---|
| Short-circuit protection | Yes |
| Reverse Polarity Protection | Yes |
| Impulsive Overvoltage Protection | Yes |
| Protection against inductive loads | Yes |

Mechanical data

| | |
|---|---|
| Dimensions | M12 x 1 / L = 64,6mm |
| Mounting | Unshielded |
| Material | AISI316L Stainless Steel |
| Housing material | AISI316L Stainless Steel |
| Weight | 30g |
| Connections | M12 Plug |
| Active Head Material | PPS |
| Tightening torque | 25Nm |
| Operating temperature | -40°C…+80°C (up to 100°C for short exposure during cleaning process) |
| Diameter/Dimension | M12 |

Test/Approvals

| | |
|---|---|
| Approvals | CE cULus ECOLAB DIVERSEY |
| EMC compatibility | IEC 60947-5-2 |
| Shocks and vibrations | Vibration IEC 60068-2-6 / Shock IEC 60068-2-27 |

| | |
|---|---|
| Degree of protection | IP68, IP69K |

Accessories


| | |
|---|---|
| Supplied Accessories | 2 nuts M12x1 |

Generical Data


| | |
|---|---|
| Dimensions | M12 x 1 / L = 64,6mm |
| Operating Temperature | -40°C…+80°C (up to 100°C for short exposure during cleaning process) |
| Mechanical Protection | IP67 |

# CONNECTIONS

Eletrical diagram






Connector





# OTHERS


Dimensions






Response curves




Installation




**Datasensing S.r.l.**
Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of printing**
04/11/2026
11:05:19