

V3

V3E1/S0-4A8F

Ind.M8,2 wires AC/DC-NC,Cable,Nsch-LD

"M8, M12, M18, M30 INDUCTIVE WITH AC/DC SUPPLY VOLTAGE"

OVERVIEW

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	4mm
Operanting distance	0…3,2mm
Standard target	12x12mm FE360
Correction Factor	copper: 0,47 / aluminium: 0,52 / brass: 0,57 / stainless steel: 0,79
Thermal drift of Sr	< 10%
Repeat Accuracy	< 5% (UB 24V Ta=23°C ±5°C)
Hysteresis	1 … 20%

Application

Description	M8 standard no-flush mount
Functions	Proximity

Outputs

Output type	MOSFET
Output Function	NC
Switching frequency	25Hz (AC) - 900Hz (DC)

Electrical data

Operating Voltage	20...120Vac/50...60Hz...20...120Vdc
Load current	5…55ma(Vac) - 5…80mA (Vdc)
Leakage current	≤ 0,55mA (Vac) - ≤ 0,40mA (Vdc)
Output voltage drop	≤ 7,5V (Vac) - ≤ 8,5V (Vdc)
Max ripple content	≤ 10%
LED indicators	Yellow LED output state
Time delay before availability	≤100ms
Short-circuit protection	Yes
Impulsive Overvoltage Protection	Yes
Inrush current	150mA/150ms (AC/DC)

0,1µF @Vmax - 1µF @Vmin	0,1µF @Vmax - 1µF @Vmin

Mechanical data

Dimensions	M8 x 1 / L = 61,9mm
Mounting	Unshielded
Material	Nickel-plated brass
Housing material	Nickel-plated brass
Weight	70g
Connections	2m PUR Cable
Active Head Material	PA4T
Tightening torque	3Nm
Operating temperature	-25°C…+70°C
Diameter/Dimension	M8

Test/Approvals

Approvals	CE cULus
EMC compatibility	IEC 60947-5-2
Shocks and vibrations	Vibration IEC 60068-2-6 / Shock IEC 60068-2-27
Degree of protection	IP67

Accessories


Supplied Accessories	2 nuts M8x1

Generical Data

Dimensions	M8 x 1 / L = 61,9mm
Operating Temperature	-25°C…+70°C
Mechanical Protection	IP67


CONNECTIONS

Eletrical diagram



OTHERS

Dimensions



Datasensing S.r.l.
Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

date of printing
04/11/2026
11:06:05