OMRON Industrial Automation



# D40ML-SS2-U-10M

RFID Magnetic Locking Safety Switch,Stainless Steel, 600N, Unique Actuator Code, 10m Cable

# Specifications

| | |
|---|---|
| **Door switch type** | RFID magnetic |
| **Guard-lock** | ✔ |
| **Coding** | Unique |
| **Material housing** | Stainless steel |
| **Ambient temperature (operating)** | -25-40 °C |
| **Holding force** | 600 N |
| **Door contacts NC** | 2 |
| **Door contacts NO** | 0 |
| **Lock monitor contacts NC** | 0 |
| **Lock monitor contacts NO** | 1 |
| **Lock/Release key type** | Not Applicable |
| **Solenoid voltage** | 24 V |
| **LED indicator** | ✔ |
| **Connection method** | Cable |
| **Cable length** | 10 m |
| **Degree of protection (IP)** | IP69K |
| **Overall length of sensor** | 96 mm |
| **Height of sensor** | 37 mm |
| **Width of sensor** | 64 mm |
| **Switch without actuator** | ✖ |
| **Lock/Release logic** | Power to lock (Solenoid lock) |

# Downloads

**CAD file**



## D40ML RFID Magnetic Locking Safety Switches

**Datasheet**

EN PDF 434 KB



## Machine Safety

**Catalogue**

EN PDF 9.91 MB



## Safety Component Selection Guide EU

**Brochure**

EN PDF 5.26 MB



## Safety Interlock Switches

**Brochure**

EN PDF 1.52 MB




## Safety Solution Advanced Guide

**Guide**

EN PDF 2.57 MB




## Safety Solution Basic Guide

**Guide**

EN PDF 14.4 MB

**TERMS OF WEBSITE USE**

This PDF document was created from the European OMRON Industrial Automation website on 4 November, 2026. Click here for terms of use.