OMRON Industrial Automation



E2E-X15B230-M1

Proximity sensor, inductive, nickel-brass, short body, M30, shielded, 15 mm, DC, 3-wire, PNP NC, M12 connector

Specifications

Size	M30
Mounting type	Quasi-flush
Sensing distance	15 mm
Overall length of sensor	58 mm
Thread length	39 mm
Material housing	Brass, nickel plated
Output type	PNP
Operation mode	NC
Connection method	Connector M12
Cable specifications	-
IO-Link function	✖
IO-Link baud rate	Not Applicable
Degree of protection (IP)	IP67/IP69K

Related products



M12 Connectors & Cordsets
Industrial connectors & cordsets for any application

Downloads


CAD file



E2E NEXT

Datasheet

EN PDF 40.3 MB



E2E(Q) - Basic Models

Index list

EN PDF 7.27 MB



E2E(Q)-XB_XC_basic_model

Instruction Sheet

EN PDF 2.28 MB



IO-Link Series

Brochure

EN PDF 7.95 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 4 November, 2026. Click here for terms of use.

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU