OMRON Industrial Automation




E5CC-RX2DBM-000

Temperature controller, 1/16DIN (48 x 48mm), 1 x relay output, 2 x auxiliary relay outputs, universal input type, 24 V AC/DC

Specifications

Size	1/16 DIN (48 x 48 mm)
Functions	ON/OFF control, PID control
Number of control loops	1
Temperature input type	B, C (WRe5-26), E, J, JPt100, K, L, N, P (PLII), Pt100, R, S, T, U
Linear analog input type	0 to 10 V, 0 to 20 mA, 0 to 5 V, 1 to 5 V, 4 to 20 mA
Temperature range	-200-2300 °C
Number of event inputs	0
Number of alarm outputs	2
Supply voltage AC	20.4-26.4 V
Supply voltage DC	20.4-26.4 V
Control output	Relay
Terminal type	Push-in

Accessories

	**E58-CIFQ2**	E5CB & E5CC and E5EC* accessory, quick link programming cable, allows direct USB connection without requirement for communications card or power supply. Also the diplay will be powered (CX-Thermo v4.4 is needed). *For E5EC front connection.
	**EST2-2C-MV4**	CX-Thermo, direct 1 to 1 connecting software (1 to several if same TC type), for programming and monitoring E5_N (version 5 & 6), E5ZN and CelciuX (EJ1)

Downloads

CAD file



Digital Temperature Controllers

Brochure

EN PDF 4.45 MB



E5CC

Instruction Manual


EN PDF 1.43 MB



E5CC-B

Instruction Manual

EN PDF 9.19 MB



E5CC-U

Instruction Manual

EN PDF 1.49 MB

E5CN-E5CC Conversion File

Software

EN ZIP 613 KB



E5_C

Instruction Sheet

EN PDF 478 KB



E5_C safety_precautions

Instruction Sheet

EN PDF 1.76 MB



E5_C/E5_C-T Digital Temperature Controller

Datasheet

EN PDF 41.1 MB



Panel Building

Brochure

EN PDF 3.11 MB

Thermac Temperature Simulation

Software

EN ZIP 16.2 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 4 November, 2026. Click here for terms of use.