OMRON Industrial Automation




E5EC-QR4A5M-000

Temperature controller, PRO, 1/8 DIN (96 x 48 mm), 1 x 12 VDC pulse/1 x Rel. OUT,4 AUX,100 to 240 VAC

Specifications

Size	1/8 DIN (96 x 48 mm)
Functions	ON/OFF control, PID control
Number of control loops	1
Temperature input type	B, C (WRe5-26), E, J, JPt100, K, L, N, P (PLII), Pt100, R, S, T, U
Linear analog input type	0 to 10 V, 0 to 20 mA, 0 to 5 V, 1 to 5 V, 4 to 20 mA
Temperature range	-200-2300 °C
Number of event inputs	0
Number of alarm outputs	4
Supply voltage AC	100-240 V
Control output	Relay, Voltage pulse
Terminal type	Screw

Accessories

	**E58-CIFQ2**	E5CB & E5CC and E5EC* accessory, quick link programming cable, allows direct USB connection without requirement for communications card or power supply. Also the diplay will be powered (CX-Thermo v4.4 is needed). *For E5EC front connection.
	**EST2-2C-MV4**	CX-Thermo, direct 1 to 1 connecting software (1 to several if same TC type), for programming and monitoring E5_N (version 5 & 6), E5ZN and CelciuX (EJ1)

Downloads

CAD file



Digital Temperature Controllers

Brochure

EN PDF 4.45 MB



E5CC

Getting Started Guide

EN PDF 5.23 MB



E5CC

Instruction Sheet

EN PDF 223 KB



E5CC/E5EC

Getting Started Guide

EN PDF 2.55 MB

E5CN-E5CC Conversion File

Software

EN ZIP 613 KB



E5EC

Instruction Sheet

EN PDF 370 KB



E5_C

Communications Manual

EN PDF 7 MB



E5_C - Digital Temperature Controllers

Users Manual

EN PDF 14.4 MB



E5_C/E5_C-T Digital Temperature Controller

Datasheet

EN PDF 41.1 MB



Panel Building

Brochure

EN PDF 3.11 MB

Thermac Temperature Simulation

Software

EN ZIP 16.2 MB



Thermac Temperature Simulation Tips and Tricks

Getting Started Guide

EN PDF 381 KB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 4 November, 2026. Click here for terms of use.