OMRON Industrial Automation




# S8VS-24024B

Power supply, 240 W, 100 to 240 VAC input, 24VDC 10 A output, DIN rail mounting, digital display with running voltage and current, peak current, and total run time function with settable alarm point

# Specifications

| | |
|---|---|
| **Type** | DIN-rail |
| **Mounting method** | DIN rail |
| **Phase** | Single |
| **Output voltage** | 24 V |
| **Power output** | 240 W |
| **Efficiency** | 88 % |
| **Rated output current** | 10 A |
| **Temperature range** | -10-60 °C |
| **Terminal type** | Screw |
| **Communication port(s)** | None |
| **Alarm function** | Transistor - sinking |
| **Number of output branches** | 1 |
| **Rated supply voltage at AC 50 Hz** | 100-240 V |
| **Allowable supply voltage AC** | 85-264 V |
| **Allowable supply voltage DC** | 80-370 V |
| **Product Width (unpacked)** | 100 mm |
| **Product Height (unpacked)** | 115 mm |
| **Product Depth (unpacked)** | 125.2 mm |

# Downloads

CAD file



**S8VS**

**Instruction Manual**

EN PDF 6.13 MB



**S8VS Switch Mode Power Supply**

**Datasheet**

EN PDF 5.86 MB

**TERMS OF WEBSITE USE**

This PDF document was created from the European OMRON Industrial Automation website on 4 November, 2026. Click here for terms of use.