






Inductive sensor

921LC2

- Basic series
- 2 mm flush



Dimensions



Technical Data

General specifications

Switching function	Normally closed (NC)	
Output type	NAMUR	
Rated operating distance	s _n	2 mm
Installation	flush	
Assured operating distance	s _a	0 ... 1.62 mm

Nominal ratings

Nominal voltage	U _o	8.2 V
Operating voltage	U _B	5 ... 15 V
Switching frequency	f	0 ... 1000 Hz
Current consumption		
Measuring plate not detected	min. 2.7 mA	
Measuring plate detected	≤ 1.8 mA	

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Technical Data

Compliance with standards and directives		
Standard conformity		
NAMUR		EN 60947-5-6:2000
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007
Approvals and certificates		
CCC approval		CCC approval / marking not required for products rated ≤36 V
Ambient conditions		
Ambient temperature		-10 ... 65 °C (14 ... 149 °F)
Mechanical specifications		
Connection type		Solder connection
Housing material		PA
Sensing face		PA
Degree of protection		IP67

Connection



Release date: 2020-03-20 Date of issue: 2020-03-30 Filename: 450097_eng.pdf