



Model Number

KHE-C01-1,0-2,0-K124

Plastic fiber optic - thru-beam

Features

- Thread M4
- High flexible

Description

Attention:

Fiber optics must not be twisted or kinked. Excessive tensile loads will lead to destruction. Contact with petrol or organic solvents must be prevented.



Accessories

K-LA06

Collimation lens, increases operating range by up to eight times, M4 thread

K-LA01

Collimation lens, increases operating range by up to four times, M2.6 thread

K-LA02

Collimation lens, right-angled, M2.6 thread

OMH-LL-M4

Mounting bracket for fiber optic cable, M4 thread

KM4-0,5

Metal protection for plastic fiber optics
M4 x 0.5 m

KM4-1,0

Metal protection for plastic fiber optics
M4 x 1.0 m

Technical data

General specifications

Detection range	SU18: 50 mm SU18/35: 210 mm SU19: 50 mm
Fiber optic length	l 2000 mm , adjustable
Fiber optic diameter	d 1 mm
Adapter form	00
End piece	thread
Bending radius	min. 1 mm
Fiber configuration	Fv see dimensions
Angle of divergence	67 °
Accessories provided	Cutter for plastic fiber optics

Ambient conditions

Ambient temperature	-55 ... 70 °C (-67 ... 158 °F)
---------------------	--------------------------------

Mechanical specifications

Material	
Optical face	plastic
Sheathing	PVC
Core	plastic
End piece	Stainless steel 1.4305 / AISI 303

Dimensions

