



Model Number

KLR-C09-1,25-3,0-K74

Plastic fiber optic - diffuse

Threading M4 / M2, 6

Features

- Coaxial
- Thread M4 / M2.6

Series

Fiber optic amplifiers

Device series	SU18 ; SU18/35 ; SU19
---------------	-----------------------

Description

Attention:

Fiber optics must not be twisted or kinked. Excessive tensile loads will lead to destruction. Contact with petrol or organic solvents must be prevented.



Accessories

K-LA06

Collimation lens, increases operating range by up to eight times, M4 thread

K-LA04

Focusing lens, light spot size approx. 0.7 mm at 10 mm, M4 thread

OMH-LL-M4

Mounting bracket for fiber optic cable, M4 thread

KM4-0,5

**Metal protection for plastic fiber optics M4
x 0.5 m**

KM4-1,0

**Metal protection for plastic fiber optics M4
x 1.0 m**

K-LA01

Collimation lens, increases operating range by up to four times, M2.6 thread

Technical data

General specifications

Sensor range		SU18: 30 mm SU18/35: 100 mm SU19: 30 mm
Fiber optic length	l	3000 mm , adjustable
Fiber optic diameter	d	1.25 mm
Adapter form		00
End piece		thread
Bending radius		min. 15 mm
Fiber configuration	Fv	see dimensions
Angle of divergence		67 °
Accessories provided		Cutter for plastic fiber optics

Ambient conditions

Ambient temperature	-55 ... 70 °C (-67 ... 158 °F)
---------------------	--------------------------------

Mechanical specifications

Mechanical Specifications	
Material	
Optical face	plastic
Sheathing	PVC
Core	plastic
End piece	Stainless steel 1.4305 / AISI 303

Dimensions

