



Model Number

LCE 04-1,6-1,0 G

Glass fiber optic - thru-beam with PVC covering
M6 threading

Features

- Thread M6

Series

Fiber optic amplifiers

Device series MLV41-LL

Description

Attention:
Fiber optics must not be twisted or kinked. Excessive tensile loads will lead to destruction. Contact with petrol or organic solvents must be prevented.



Technical data

General specifications

Fiber optic length	l	1000 mm
Fiber optic diameter	d	2.7 mm
Adapter form		04
End piece		thread
Bending radius		min. 10 mm
Fiber bundle diameter		1.8 mm optical face: 2.5 mm ²
Angle of divergence		approx. 68 °


Ambient conditions

Ambient temperature	-20 ... 85 °C (-4 ... 185 °F) [Adapter]
	-20 ... 85 °C (-4 ... 185 °F) [End head and Covering]
Storage temperature	-20 ... 85 °C (-4 ... 185 °F)

Mechanical specifications

Protection degree	IP65
Material	
Optical face	glass
Sheathing	PVC
Core	Glass fiber
End piece	Stainless steel 1.4305 / AISI 303
Adapter	PVC
Extraction force	at probe at 20°C: 120 N

Dimensions



Release date: 2013-09-16 13:31 Date of issue: 2013-09-16 416002_eng.xml