



Model Number

LLR 04-1,6-0,4-W C3

Glass fiber optic - diffuse with metal silicone covering

Features

- Chemical-resistant

Series

Fiber optic amplifiers

Device series MLV41-LL

Description


Attention:
Fiber optics must not be twisted or kinked. Excessive tensile loads will lead to destruction. Contact with petrol or organic solvents must be prevented.



Technical data

General specifications		
Fiber optic length	l	400 mm
Fiber optic diameter	d	7.3 mm
Adapter form		04
End piece		Thread / cylindrical right angle
Bending radius		min. 20 mm
Fiber bundle diameter		1.8 mm optical face: 2.5 mm ²
Fiber configuration	Fv	optical seperated
Angle of divergence		approx. 68 °
Ambient conditions		
Ambient temperature		-20 ... 85 °C (-4 ... 185 °F) [Adapter] -40 ... 180 °C (-40 ... 356 °F) [End head and Covering]
Storage temperature		-20 ... 85 °C (-4 ... 185 °F)
Mechanical specifications		
Protection degree		IP65
Material		
Optical face		glass
Sheathing		Metal-silicon
Core		Glass fiber
End piece		Stainless steel 1.4305 / AISI 303
Adapter		PVC
Extraction force		at probe at 20°C: 120 N

Dimensions



Release date: 2013-09-16 13:30 Date of issue: 2013-09-16 415657_eng.xml