



Model Number

LMR 18-2x1,6-4,0-K3

Features

- Sturdy metallic version
- Chemical-resistant
- Thread M4

Series

Fiber optic amplifiers

Device series	VL18LL VariKont M
---------------	----------------------

Description

Attention:

Fiber optics must not be twisted or kinked. Excessive tensile loads will lead to destruction. Contact with petrol or organic solvents must be prevented.



Technical data

General specifications

Fiber optic length	l	4000 mm
Fiber optic diameter	d	5 mm
Adapter form		18
End piece		thread
Bending radius		min. 20 mm
Fiber bundle diameter		active 1.6 mm optical face: 2 mm ²
Fiber configuration	Fv	optical seperated
Angle of divergence		68 °


Ambient conditions

Ambient temperature	-20 ... 85 °C (-4 ... 185 °F) [Adapter] -50 ... 200 °C (-58 ... 392 °F) [End head and Covering]
Storage temperature	-20 ... 85 °C (-4 ... 185 °F)

Mechanical specifications

Degree of protection	IP40
Material	
Optical face	glass
Sheathing	metal
Core	Glass fiber
End piece	Stainless steel 1.4305 / AISI 303
Adapter	PBT
Extraction force	at probe at 20°C: 120 N

Dimensions



Release date: 2015-06-18 08:10 Date of issue: 2015-06-18 092885_eng.xml