



Inductive sensor
NBB10-30GM50-WO-10M



Dimensions




Technical Data

General specifications		
Switching function		Normally closed (NC)
Output type		Two-wire
Rated operating distance	s _n	10 mm
Installation		flush
Output polarity		AC
Assured operating distance	s _a	0 ... 8.1 mm
Actual operating distance	s _r	9 ... 11 mm
Reduction factor r _{Al}		0.33
Reduction factor r _{Cu}		0.28
Reduction factor r ₃₀₄		0.81
Nominal ratings		
Operating voltage	U _B	20 ... 253 V

Technical Data

Switching frequency	f	0 ... 20 Hz
Hysteresis	H	typ. 5 %
Voltage drop	U _d	< 5 V (I _L > 50 mA); < 8 V (I _L < 50 mA)
Momentary current (20 ms, 0.1 Hz)		0 ... 1600 mA
Operating current	I _L	5 ... 200 mA
Off-state current	I _r	0 ... 1.7 mA
Operating voltage indicator		LED, green
Switching state indicator		LED, yellow
Compliance with standards and directives		
Standard conformity		
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
CCC approval		Certified by China Compulsory Certification (CCC)
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		cabl PVC , 10 m
Core cross-section		0.75 mm ²
Housing material		brass, nickel-plated
Sensing face		PBT
Degree of protection		IP67
Note		1) In the temperature range below 0 °C, permissible operating voltage U _b 80...253 V Safety fuse ≤ 0.8 A (quick-blow) according to IEC 60127-2 Sheet 1 Recommendation: after a short circuit, check that the device is functioning correctly.

Connection



Accessories

	BF 30	Mounting flange, 30 mm
	EXG-30	Quick mounting bracket with dead stop