





## Inductive sensor NBB15-U1-E2

- Sensor head bidirectional and rotatable
- 4 LEDs indicator for 360° visibility
- 15 mm flush



### Dimensions



### Technical Data

#### General specifications

|                            |       |                             |
|----------------------------|-------|-----------------------------|
| Switching function         |       | Normally open (NO)          |
| Output type                |       | PNP                         |
| Rated operating distance   | $s_n$ | 15 mm                       |
| Installation               |       | flush                       |
| Output polarity            |       | DC                          |
| Assured operating distance | $s_a$ | 0 ... 12.15 mm              |
| Actual operating distance  | $s_r$ | 13.5 ... 16.5 mm typ. 15 mm |
| Reduction factor $r_{AI}$  |       | 0.33                        |

Release date: 2020-03-23 Date of issue: 2020-03-30 Filename: 194767\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com


**PEPPERL+FUCHS**

## Technical Data

|                                                 |       |                                                                                                                                            |
|-------------------------------------------------|-------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Reduction factor $r_{Cu}$                       |       | 0.31                                                                                                                                       |
| Reduction factor $r_{304}$                      |       | 0.74                                                                                                                                       |
| Reduction factor $r_{Brass}$                    |       | 0.41                                                                                                                                       |
| Output type                                     |       | 3-wire                                                                                                                                     |
| <b>Nominal ratings</b>                          |       |                                                                                                                                            |
| Operating voltage                               | $U_B$ | 10 ... 30 V                                                                                                                                |
| Switching frequency                             | $f$   | 0 ... 560 Hz                                                                                                                               |
| Hysteresis                                      | $H$   | typ. 5 %                                                                                                                                   |
| Reverse polarity protection                     |       | reverse polarity protected                                                                                                                 |
| Short-circuit protection                        |       | pulsing                                                                                                                                    |
| Voltage drop                                    | $U_d$ | $\leq 2$ V                                                                                                                                 |
| Operating current                               | $I_L$ | 0 ... 200 mA                                                                                                                               |
| Off-state current                               | $I_r$ | 0 ... 0.5 mA typ. 0.01 mA                                                                                                                  |
| No-load supply current                          | $I_0$ | $\leq 20$ mA                                                                                                                               |
| Time delay before availability                  | $t_v$ | 80 ms                                                                                                                                      |
| Operating voltage indicator                     |       | LED, green                                                                                                                                 |
| Switching state indicator                       |       | LED, yellow                                                                                                                                |
| <b>Functional safety related parameters</b>     |       |                                                                                                                                            |
| MTTF <sub>d</sub>                               |       | 1289 a                                                                                                                                     |
| Mission Time ( $T_M$ )                          |       | 20 a                                                                                                                                       |
| Diagnostic Coverage (DC)                        |       | 0 %                                                                                                                                        |
| <b>Compliance with standards and directives</b> |       |                                                                                                                                            |
| Standard conformity                             |       |                                                                                                                                            |
| Standards                                       |       | EN 60947-5-2:2007<br>EN 60947-5-2/A1:2012<br>IEC 60947-5-2:2007<br>IEC 60947-5-2 AMD 1:2012                                                |
| <b>Approvals and certificates</b>               |       |                                                                                                                                            |
| EAC conformity                                  |       | TR CU 020/2011                                                                                                                             |
| UL approval                                     |       | cULus Listed, General Purpose                                                                                                              |
| CCC approval                                    |       | CCC approval / marking not required for products rated $\leq 36$ V                                                                         |
| <b>Ambient conditions</b>                       |       |                                                                                                                                            |
| Ambient temperature                             |       | -25 ... 85 °C (-13 ... 185 °F)                                                                                                             |
| <b>Mechanical specifications</b>                |       |                                                                                                                                            |
| Connection type                                 |       | screw terminals                                                                                                                            |
| Information for connection                      |       | A maximum of two conductors with the same core cross section may be mounted on one terminal connection!<br>tightening torque 1.2 Nm + 10 % |
| Core cross-section                              |       | up to 2.5 mm <sup>2</sup>                                                                                                                  |
| Minimum core cross-section                      |       | without wire end ferrule 0.5 mm <sup>2</sup> , with connector sleeves 0.34 mm <sup>2</sup>                                                 |
| Maximum core cross-section                      |       | without wire end ferrule 2.5 mm <sup>2</sup> , with connector sleeves 1.5 mm <sup>2</sup>                                                  |
| Housing material                                |       | PA/metal with epoxy powder coating                                                                                                         |
| Sensing face                                    |       | PA                                                                                                                                         |
| Housing base                                    |       | plastic                                                                                                                                    |
| Degree of protection                            |       | IP68 / IP69K                                                                                                                               |
| Mass                                            |       | 225 g                                                                                                                                      |
| Note                                            |       | Tightening torque: 1.8 Nm (housing)                                                                                                        |

Release date: 2020-03-23 Date of issue: 2020-03-30 Filename: 194767\_eng.pdf

Connection



Accessories

|                                                                                   |                  |                                       |
|-----------------------------------------------------------------------------------|------------------|---------------------------------------|
|  | <b>MHW 01</b>    | Modular mounting bracket              |
|  | <b>V1-M20-80</b> | Receptacles, M12/M20; plastic version |

Release date: 2020-03-23 Date of issue: 2020-03-30 Filename: 194767\_eng.pdf