





Inductive sensor

NBB2-6,5S16-E2-Y273690

- Basic series
- Increased operating distance



Dimensions




Technical Data

General specifications			
Switching function		Normally open (NO)	
Output type		PNP	
Rated operating distance	s _n	2 mm	
Installation		flush	
Output polarity		DC	
Assured operating distance	s _a	0 ... 1.62 mm	
Reduction factor r _{AI}		0.3	
Reduction factor r _{Cu}		0.25	

Technical Data

Reduction factor r_{304}		0.7
Reduction factor r_{Si37}		1
Reduction factor r_{Brass}		0.4
Nominal ratings		
Operating voltage	U_B	10 ... 30 V
Switching frequency	f	0 ... 5000 Hz
Hysteresis	H	$\leq 10 \%$
Reverse polarity protection		reverse polarity protected
Short-circuit protection		pulsing
Voltage drop	U_d	$\leq 2 \text{ V}$
Operating current	I_L	0 ... 200 mA
Off-state current	I_r	$\leq 0.1 \text{ mA}$
No-load supply current	I_0	$\leq 10 \text{ mA}$
Switching state indicator		LED
Compliance with standards and directives		
Standard conformity		
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CCC approval		CCC approval / marking not required for products rated $\leq 36 \text{ V}$
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		cabl PVC , 2 m
Core cross-section		0.14 mm ²
Housing material		Stainless steel 1.4305 / AISI 303
Sensing face		PA 12
Degree of protection		IP67

Connection



Accessories

	BF 6,5	Mounting flange, 6.5 mm
---	---------------	-------------------------