

Inductive sensor


NBB2-8GH40-E0-V3



- Increased operating distance
- Materials used compliant with FDA
- Housing with stainless steel (V4A; 1.4435)



Dimensions



Technical Data

General specifications			
Switching function		Normally open (NO)	
Output type		NPN	
Rated operating distance	s _n	2 mm	
Installation		flush	
Output polarity		DC	
Assured operating distance	s _a	0 ... 1.62 mm	
Reduction factor r _{AI}		0.25	
Reduction factor r _{Cu}		0.2	

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Reduction factor r_{304}		0.63
Reduction factor r_{Brass}		0.31
Nominal ratings		
Operating voltage	U_B	10 ... 30 V
Switching frequency	f	0 ... 1500 Hz
Hysteresis	H	typ. 5 %
Reverse polarity protection		reverse polarity protected
Short-circuit protection		pulsing
Voltage drop	U_d	≤ 3 V
Operating current	I_L	0 ... 100 mA
Off-state current	I_r	0 ... 0.5 mA typ. 10 μ A at 25 °C
No-load supply current	I_o	≤ 15 mA
Switching state indicator		Multihole-LED, yellow
Compliance with standards and directives		
Standard conformity		
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
CCC approval		CCC approval / marking not required for products rated ≤ 36 V
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		M8 x 1 connector, 3-pin
Housing material		Stainless steel 1.4435 / AISI 316L
Sensing face		LCP, (conforms with FDA)
Degree of protection		IP67
Mass		7 g

Connection



Connection Assignment



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
3	BU	(blue)
4	BK	(black)

Accessories

	BF 8	Mounting flange, 8 mm
	V3-WMV4A-5M-PUR	Female cordset single-ended, M8, stainless steel V4A, 3-pin, PUR cable
	V3-WM-2M-PUR	Female cordset single-ended, M8, 3-pin, PUR cable

Release date: 2020-03-23 Date of issue: 2020-03-30 Filename: 213443_eng.pdf