




Inductive sensor NBB7-F104M-A2-200MM-V1

- 7 mm flush
- 4-wire DC
- Metal housing



Dimensions



Technical Data

General specifications

Switching function		complementary
Output type		PNP
Rated operating distance	s_n	7 mm
Installation		flush
Output polarity		DC
Output type		4-wire

Nominal ratings

Operating voltage	U_B	10 ... 30 V DC
Switching frequency	f	150 Hz
Reverse polarity protection		reverse polarity protected
Short-circuit protection		pulsing
Voltage drop	U_d	≤ 2.5 V
Operating current	I_L	200 mA
Off-state current	I_r	≤ 80 μ A
No-load supply current	I_0	≤ 15 mA
Switching state indicator		LED

Compliance with standards and directives

Release date: 2020-05-13 Date of issue: 2020-05-13 Filename: 909688_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**


Technical Data

Standard conformity		
Standards	IEC / EN 60947-5-2:2004	
Approvals and certificates		
UL approval	cULus Listed, General Purpose	
CCC approval		CCC approval / marking not required for products rated ≤36 V
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		Cable connector M12 x 1 , 4-pin with PUR cable 200 mm
Core cross-section	0.14 mm²	
Housing material		GD-Zn
Sensing face	PA 12	
Degree of protection		IP67

Connection



Connection Assignment



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
2	WH	(white)
3	BU	(blue)
4	BK	(black)

Accessories

	V1-G-BK2M-PVC-U	Female cordset, M12, 4-pin, PVC cable
	V1-W-BK2M-PVC-U	Female cordset, M12, 4-pin, PVC cable