



NBB8-F33-A2-M1-Y293755



- 8 mm flush
- 4-wire DC
- Raised EMC resistance 36 V/m
- E1-Type approval



Dimensions



Technical Data

General specifications

Switching function		complementary
Output type		PNP
Rated operating distance	s _n	8 mm
Installation		flush
Output polarity		DC
Assured operating distance	s _a	0 ... 6.48 mm
Reduction factor r _{Al}		0.3
Reduction factor r _{Cu}		0.2
Reduction factor r ₃₀₄		0.6
Output type		3-wire

Nominal ratings

Operating voltage	U _B	10 ... 30 V DC
Switching frequency	f	0 ... 350 Hz
Hysteresis	H	typ. 5 %
Reverse polarity protection		reverse polarity protected

Release date: 2020-03-24 Date of issue: 2020-03-30 Filename: 293755_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sq.pepperl-fuchs.com




Technical Data

Short-circuit protection		pulsing
Voltage drop	U_d	$\leq 3 \text{ V}$
Operating current	I_L	0 ... 200 mA
Off-state current	I_r	0 ... 0.5 mA
No-load supply current	I_0	$\leq 25 \text{ mA}$
Time delay before availability	t_v	$\leq 5 \text{ ms}$
Switching state indicator		LED yellow
Functional safety related parameters		
MTTF _d		1240 a
Mission Time (T_M)		20 a
Diagnostic Coverage (DC)		0 %
Compliance with standards and directives		
Standard conformity		
Standards		EN 60947-5-2:2007 EN 60947-5-2/A1:2012 IEC 60947-5-2:2007 IEC 60947-5-2 AMD 1:2012
Approvals and certificates		
UL approval		cULus Listed, Class 2 Power Source, Type 1 enclosure
E1 Type approval		10R-04
Ambient conditions		
Ambient temperature		-35 ... 70 °C (-31 ... 158 °F)
Storage temperature		-40 ... 85 °C (-40 ... 185 °F)
Mechanical specifications		
Connection type		Cable connector M12 x 1 , PUR , L = 0.3 m
Core cross-section		0.5 mm ²
Housing material		PBT
Sensing face		PBT
Degree of protection		IP67 / IP69K
Note		Tightening torque: 5 Nm

Connection



Connection Assignment



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
2	WH	(white)
3	BU	(blue)
4	BK	(black)