

Inductive sensor


NJ2-D-E02-2.062-V1

- 4-wire DC
- Weld Immune
- Sensing range 2 mm
- 3000 psi rating

Cylinder Position Switch



Dimensions



Technical Data

General specifications

Switching function	Normally open (NO)	
Output type	PNP/NPN	
Rated operating distance	s_n	2 mm
Installation	flush	
Output polarity	DC	
Assured operating distance	s_a	0 ... 1.62 mm
Reduction factor r_{AI}	0.4	
Reduction factor r_{304}	0.85	

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS


Technical Data

Output type		4-wire
Nominal ratings		
Operating voltage	U _B	10 ... 30 V DC
Switching frequency	f	30 Hz
Hysteresis	H	10 ... 20 typ. 15 %
Reverse polarity protection		yes
Short-circuit protection		yes
Voltage drop	U _d	≤ 2 V DC
Operating current	I _L	≤ 200 mA
Off-state current	I _r	≤ 100 μA
No-load supply current	I ₀	≤ 35 mA
Mag. Field strength, AC fields		250 mT
Mag. Field strength, DC fields		100 mT
Limit data		
Operating pressure dynamically		3000 psi
Indicators/operating means		
LED green		Power on
LED yellow		Output status
Standard conformity		
Standards		EN 60947-5-2
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		Connector plug M12 x 1 , 4-pin
Degree of protection		IP67
Material		Housing: zinc Probe: aluminum
Note		X = 2.062 in (52.4 mm)

Connection



Connection Assignment



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
2	WH	(white)
3	BU	(blue)
4	BK	(black)

Additional Information

NPT Type Mounting Holes:
1000 and 3000 psi NPT Types:
Mounting hole screw thread shall be 1/4" - 20.
Minimum thread engagement depth is 0.250" (6.35 mm)
Hole spacing is 35 mm center to center.

Mounting Screws:
Standard 1000 and 3000 psi models use two, self-locking 1/4"-20 socket head cap screws (provided).
Recommended tightening torque: 150 in lb (16.95 N-m).

Important: When using spacers, make certain to maintain the 0.250" (6.35 mm) minimum mounting screw thread engagement.

Diagram illustrating the NPT Type Mounting Holes. It shows a top view of the mounting plate with two holes. Labels indicate: 'Sensor through hole', 'Mounting hole (Ø)', 'Mounting hole spacing', and 'Cylinder End Cap Overhead View'.

Accessories

	V1-G-2M-PVC	Female cordset, M12, 4-pin, PVC cable
	SPACER 0.160 TO 0.375 :	Spacer for cylinder switches X.XXX"
	SPACER 0.380 TO 0.875 :	Spacer for cylinder switches X.XXX"
	SPACER 0.880 TO 1.750 :	Spacer for cylinder switches X.XXX"

Release date: 2020-05-21 Date of issue: 2020-05-21 Filename: 904467_eng.pdf