


Inductive sensor


NMB3-8GM65-E2-V3



- Stainless steel sensing face
- 3 mm flush
- Increased operating distance



Dimensions



Technical Data

General specifications		
Switching function		Normally open (NO)
Output type		PNP
Rated operating distance	s_n	3 mm
Installation		flush
Output polarity		DC
Assured operating distance	s_a	0 ... 2.43 mm
Reduction factor r_{Al}		0.3
Reduction factor r_{Cu}		0.2
Reduction factor r_{304}		0.8
Reduction factor r_{Si37}		1
Nominal ratings		
Operating voltage	U_B	10 ... 30 V DC

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Switching frequency	f	0 ... 360 Hz
Hysteresis	H	5 ... 15 typ. 10 %
Reverse polarity protection		yes
Short-circuit protection		yes
Voltage drop	U _d	≤ 2 V
Operating current	I _L	≤ 100 mA
Current consumption		≤ 10 mA
Off-state current	I _r	≤ 10 µA
No-load supply current	I ₀	≤ 15 mA
Indicators/operating means		
Operation indicator		LED red: output
Standard conformity		
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
CCC approval		CCC approval / marking not required for products rated ≤36 V
Ambient conditions		
Ambient temperature		0 ... 75 °C (32 ... 167 °F)
Mechanical specifications		
Connection type		Connector M8 x 1 , 3-pin
Housing material		Stainless steel 1.4305 / AISI 303
Sensing face		Stainless steel 1.4305 / AISI 303
Degree of protection		IP67

Connection



Connection Assignment



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
3	BU	(blue)
4	BK	(black)

Release date: 2020-03-24 Date of issue: 2020-03-30 Filename: 912996_eng.pdf

Accessories

	V3-WM-2M-PUR	Female cordset single-ended, M8, 3-pin, PUR cable
---	--------------	---

Release date: 2020-03-24 Date of issue: 2020-03-30 Filename: 912996_eng.pdf