




Inductive sensor

NMB6-F104M-E2-NFE-200MM-V1

- Sensing range 6 mm
- Nonferrous targets
- Stainless steel sensing face
- 200 mm M12 male cordset with PUR jacket
- Power and output LEDs



Dimensions




Technical Data

General specifications		
Switching function		Normally open (NO)
Output type		PNP
Rated operating distance	S _n	6 mm
Installation		flush
Assured operating distance	S _a	0 ... 4.86 mm
Actuating element		Nonferrous targets
Reduction factor r _{Al}		1
Reduction factor r _{Cu}		1.1
Reduction factor r ₃₀₄		0
Reduction factor r _{St37}		0
Reduction factor r _{Brass}		0.9
Output type		3-wire
Nominal ratings		
Operating voltage	U _B	10 ... 30 V DC
Switching frequency	f	20 Hz


Technical Data

Hysteresis	H	5 ... 15 typ. 10 %
Reverse polarity protection		reverse polarity protected
Short-circuit protection		yes
Voltage drop	U _d	≤ 2 V
Operating current	I _L	≤ 100 mA
Current consumption		≤ 22 mA
Off-state current	I _r	≤ 10 µA
Indicators/operating means		
Operation indicator		Dual LED Green: power Yellow: output
Standard conformity		
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CCC approval		CCC approval / marking not required for products rated ≤36 V
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		Cable connector M12 x 1 , 3-pin with PUR cable 200 mm
Core cross-section		0.34 mm ²
Housing material		Stainless steel 1.4305 / AISI 303
Degree of protection		IP67

Connection



Connection Assignment



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
3	BU	(blue)
4	BK	(black)