




Inductive sensor

NMB8-30GM80-US-FE

- Stainless steel sensing face
- Sensing range 8 mm
- 2-wire AC/DC
- Ferrous targets



Dimensions



Technical Data

General specifications			
Switching function		Normally open (NO)	
Output type		Two-wire	
Rated operating distance	S _n	8 mm	
Installation		flush	
Output polarity		AC/DC	
Assured operating distance	S _a	0 ... 6.48 mm	
Actuating element		Ferrous targets	
Reduction factor r _{Al}		0	
Reduction factor r _{Cu}		0	
Reduction factor r ₃₀₄		0.4 - 0.7	
Reduction factor r _{Si37}		1	
Reduction factor r _{Brass}		0	

Technical Data

Nominal ratings

Operating voltage DC	U_B	20 ... 300 V
Operating voltage AC	U_B	20 ... 250 V
Switching frequency	f	10 Hz
Hysteresis	H	3 ... 15 typ. 5 %
Reverse polarity protection		reverse polarity tolerant
Short-circuit protection		yes
Voltage drop	U_d	≤ 7 V
Operating current	I_L	8 ... 200 mA
Off-state current	I_r	≤ 1.3 mA
Error indicator		LED, green/yellow (Alternate Flashing) - Short circuit/overload indication

Indicators/operating means

Operation indicator		Dual LED Green: power Yellow: output
---------------------	--	--

Compliance with standards and directives

Standard conformity		
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007

Approvals and certificates

UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
CCC approval		Certified by China Compulsory Certification (CCC)


Ambient conditions

Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
---------------------	--	--------------------------------

Mechanical specifications

Connection type		cabl PUR , 2 m
Core cross-section		0.5 mm ²
Housing material		Stainless steel 1.4305 / AISI 303
Sensing face		Stainless steel 1.4305 / AISI 303
Degree of protection		IP67

Connection



Accessories

	AB-30	Mounting aid
---	--------------	--------------