




Inductive sensor

NMB8-30GM85-US-FE-V93

- Stainless steel sensing face
- Sensing range 8 mm
- 2-wire AC/DC
- Ferrous targets



Dimensions



Technical Data

General specifications		
Switching function		Normally open (NO)
Output type		Two-wire
Rated operating distance	s _n	8 mm
Installation		flush
Output polarity		AC/DC
Assured operating distance	s _a	0 ... 6.48 mm
Actuating element		Ferrous targets
Reduction factor r _{Al}		0
Reduction factor r _{Cu}		0
Reduction factor r ₃₀₄		0.4 - 0.7
Reduction factor r _{St37}		1
Reduction factor r _{Brass}		0
Nominal ratings		
Operating voltage DC	U _B	20 ... 300 V
Operating voltage AC	U _B	20 ... 250 V
Switching frequency	f	10 Hz
Hysteresis	H	3 ... 15 typ. 5 %
Reverse polarity protection		reverse polarity tolerant
Short-circuit protection		yes
Voltage drop	U _d	≤ 7 V
Operating current	I _L	8 ... 200 mA

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS


Technical Data

Off-state current	I _r	≤ 1.3 mA
Error indicator	LED, green/yellow (Alternate Flashing) - Short circuit/overload indication	
Indicators/operating means		
Operation indicator	Dual LED Green: power Yellow: output	
Compliance with standards and directives		
Standard conformity		
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
CCC approval		Certified by China Compulsory Certification (CCC)
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		Connector 7/8"-16 UN , 3-pin
Housing material		Stainless steel 1.4305 / AISI 303
Sensing face		Stainless steel 1.4305 / AISI 303
Degree of protection		IP67

Connection



Connection Assignment



Wire colors

1	GN	(green)
2	BK	(black)
3	WH	(white)

Accessories

	AB-30	Mounting aid
--	--------------	--------------