


Properties

- INTERBUS interface
- Data rate up to 2 MBaud
- Connector version
- Infrared light

Your Benefit

- Integral alignment aid LED simplifies setup
- Easy installation due to quick clamp tool-less mounting
- LED bar display indicates signal strength



Technical Data

*For detailed data and product description refer to the data sheets at **www.pepperl-fuchs.com***

General Data	
Light type	modulated infrared light
Diameter of the light spot	2 m at a distance of 100 m
Interface type	RS 422 , galvanically isolated
Operating voltage	18 ... 30 V DC
No-load supply current	200 mA
Data rate	0 ... 2 MBit/s
Pre-fault indication output	1 PNP (switches if there is sufficient stability control) short-circuit protected, max. 200 mA
Housing	ABS / PC
Optical face	plastic
Protection degree	IP65
Connection	4-pin, M12x1 connector, standard (supply) , 5-pin, M12x1 connector, B-coded (Remote Bus In) , 5-pin, M12x1 socket, B-coded (Remote Bus Out)

Model Number		LS610-DA-IBS/F1	LS610-DA-IBS/F1/146	LS610-DA-IBS/F2	LS610-DA-IBS/F2/146	LS610-DA-IBS/F1/35	LS610-DA-IBS/F1/35/146	LS610-DA-IBS/F2/35	LS610-DA-IBS/F2/35/146
Threshold detection range	140 m	●	●	●	●				
	260 m					●	●	●	●
Effective detection range	0 ... 120 m	●	●	●	●				
	0 ... 240 m					●	●	●	●
Operation frequency	F1 = 8.25 MHz	●	●			●	●		
	F2 = 12.5 MHz			●	●			●	●
Ambient temperature	-10 ... 50 °C (14 ... 122 °F)	●		●		●		●	
	-30 ... 50 °C (-22 ... 122 °F) , For use in dry cold		●		●		●		●

Dimensions	
Length L [mm]	171
Width W [mm]	170
Height H [mm]	90

Accessories


This and more accessories can be found in chapter 10

See pages from 974 ... for cordsets See pages 1074 ... for mounting aids

OMH-LS610-05	Mounting bracket for optical data coupler and distance measurement devices
V15SB-G	Cable connector, M12, for PROFIBUS, adjustable
V15B-G	Cable socket, M12, for PROFIBUS, adjustable
V15-G-PG9	Cable socket, M12, 5-pin, ready for assembly
Funktionserdung LS610/ VDM100 Zubehoer	Function grounding for LS610 / LS611 / VDM100 series
Schutzkappe LS610 Zubehoer	M12 protective cap set (connector + socket) for series LS610 / LS611
OMH-LS610-01	Mounting bracket for optical data coupler
OMH-LS610-02	Direct mounting set consisting of 4 x M4 threaded inserts
OMH-LS610-03	Mounting bracket with deviation mirror for optical data coupler
OMH-LS610-04	
OMH-LS610-31	Mounting bracket for optical data coupler and distance measurement devices
OMH-LS610-32	Mounting bracket for optical data coupler and distance measurement devices

Electrical Connection





Date of issue: 2012/08/13

Consider the General Notes on the Information in the Pepperl+Fuchs Product Catalogs
Copyright Pepperl+Fuchs
Pepperl+Fuchs Group www.pepperl-fuchs.com
USA: +1 330 486 0001 fa-info@us.pepperl-fuchs.com
Germany: +49 621 776-4411 fa-info@de.pepperl-fuchs.com
Singapore: +65 6779 9091 fa-info@sg.pepperl-fuchs.com
PEPPERL+FUCHS SENSING YOUR NEEDS