

Properties

- Up to 6000 mm sensing range versions
- DC, analog outputs
- Ø30 mm cylindrical housing
- Connector version

Your Benefit


- Potentiometer-free configuration via programming plug or ULTRA3000 software

Further Products

In this series, we offer the following additional products:

UCC1000-30GM-IUR2-V15

Technical data like UC2000-30GM-IUR2-V15 but:
Sensing range: 1000 mm
Transducer: chemical resistant PTFE coated



Technical Data

*For detailed data and product description refer to the data sheets at **www.pepperl-fuchs.com***

General Data	
Operating voltage	10 ... 30 V DC , ripple 10 %$_{SS}$
Power consumption	≤ 900 mW
Interface type	RS 232, 9600 Bit/s , no parity, 8 data bits, 1 stop bit
Output type	1 current output 4 ... 20 mA 1 voltage output 0 ... 10 V
Deviation of the characteristic curve	≤ 0.2 % of full-scale value
Synchronization	bi-directional
Material	
Housing	stainless steel (1.4305 / AISI 303), PBT plastic parts
Transducer	epoxy resin/hollow glass sphere mixture; polyurethane foam
Protection degree	IP65
Connection type	Device connector M12 x 1 , 5-pin



Model Number		UC300-30GM-IUR2-V15	UC500-30GM-IUR2-V15	UC2000-30GM-IUR2-V15	UC4000-30GM-IUR2-V15	UC6000-30GM-IUR2-V15
Sensing range	15 ... 300 mm	●				
	30 ... 500 mm		●			
	80 ... 2000 mm			●		
	200 ... 4000 mm				●	
	350 ... 6000 mm					●
Transducer frequency	approx. 380 kHz	●	●			
	approx. 180 kHz			●		
	approx. 85 kHz				●	
	approx. 65 kHz					●
Resolution	evaluation range [mm]/4000, but ≥ 0.05 mm	●	●			
	evaluation range [mm]/4000, but ≥ 0.35 mm			●	●	●
Ambient temperature	0 ... 70 °C (32 ... 158 °F)	●				
	-25 ... 70 °C (-13 ... 158 °F)		●	●	●	●
Approvals and Certificates						
UL approval	cULus Listed, General Purpose	●	●	●	●	●
CSA approval	cCSAus Listed, General Purpose	●	●	●	●	●

Dimensions				
Length L [mm]	114		128	132
Diameter D [mm]	30			
Transducer diameter D_1 [mm]	30		40	73
Transducer length l_1 [mm]	0		25	32,5
Thread length l_t [mm]	92		81	77,5
Connector area l_c [mm]	10			
LED position	Pos. A			
Temperature / program plug	Pos. A , 27.5 mm			

Accessories

This and more accessories can be found in chapter 3.5 from page 676
See pages from 974 ... for cordsets See pages 1074 ... for mounting aids


BF 30	Mounting flange, 30 mm
BF 30-F	Mounting flange with dead stop, 30 mm
BF 5-30	Universal mounting bracket for cylindrical sensors with a diameter of 5 ... 30 mm
UC-30GM-R2	Programming cable
ULTRA3000	Software for ultrasonic sensors, comfort line
V15-G-2M-PVC	Cable socket, M12, 5-pin, PVC cable
V15-W-2M-PUR	Cable socket, M12, 5-pin, PUR cable

Electrical Connection




UC300-30GM-IUR2-V15
UC500-30GM-IUR2-V15
UC2000-30GM-IUR2-V15
UC4000-30GM-IUR2-V15
UC6000-30GM-IUR2-V15
UCC1000-30GM-IUR2-V15

Standard symbol/Connection:
(version IU)



Core colors in accordance with EN 60947-5-2.



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
2	WH	(white)
3	BU	(blue)
4	BK	(black)
5	GY	(gray)

Date of issue: 07/30/2012

Consider the General Notes on the Information in the Pepperl+Fuchs Product Catalogs
Copyright Pepperl+Fuchs
Pepperl+Fuchs Group www.pepperl-fuchs.com
USA: +1 330 486 0001 fa-info@us.pepperl-fuchs.com
Germany: +49 621 776-4411 fa-info@de.pepperl-fuchs.com
Singapore: +65 6779 9091 fa-info@sg.pepperl-fuchs.com
PEPPERL+FUCHS SENSING YOUR NEEDS