


Inductive ring sensor

RB15-14-E2-BI-Y97927

- 15 mm inside diameter
- Basic series
- Bistable
- Direction detection



Dimensions



Technical Data

General specifications		
Switching function		Normally open (NO)
Output type		PNP
Installation		
Output polarity		DC
Inside diameter		15 mm
Measuring cone		6 mm
Material		1.4401
Passage speed	v	≤ 10 m/s
Nominal ratings		
Operating voltage	U _B	10 ... 30 V
Reverse polarity protection		reverse polarity protected
Short-circuit protection		pulsing
Output voltage		
Traverse A		1 V
Traverse B		U _B - 3 V
Power ON		1 V
Voltage drop	U _d	≤ 1.5 V

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Operating current	I_L	0 ... 100 mA
No-load supply current	I_0	≤ 10 mA
Compliance with standards and directives		
Standard conformity		
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		cablE PUR , 2 m
Core cross-section		0.14 mm ²
Cable diameter		3 mm
Housing material		PBT
Degree of protection		IP67

Connection

