





Cable socket, shielded V15-G-10M-PUR-ABG5

- Shield connected to pin 5
- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Degree of protection IP67 / IP68 / IP69K
- Halogen-free

Female cordset, M12, 4-pin, PUR cable, screen on pin 5

Dimensions



Technical Data

General specifications

Number of pins	4 + shield
Connection 1	socket
Construction type 1	straight
Threading 1	M12
Connection 2	cable end

Electrical specifications

Operating voltage	U_B	max. 48 V AC / 60 V DC
Operating current	I_B	max. 4 A
Contact resistance		< 10 mΩ

Compliance with standards and directives

Standard conformity	
Degree of protection	EN 60529:2000
Standards	IEC 61076-2-101:2008 Limited to a maximum of 500 VDC for insulation strength and surge voltage strength
Flammability	Grip: UL 94
Specification	connector M12 x 1 : IEC 61076-2-101

Release date: 2020-08-26 Date of issue: 2020-08-26 Filename: 70126954_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Technical Data

Ambient conditions

Ambient temperature	Body: -40 ... 90 °C (-40 ... 194 °F) cable, flexing: -25 ... 80 °C (-13 ... 176 °F) cable, fixed: -25 ... 80 °C (-13 ... 176 °F)
---------------------	--

Pollution degree	3
------------------	---

Mechanical specifications

Contact elements	spring-loaded contact socket
------------------	------------------------------

Pin diameter	1 mm
--------------	------

Degree of protection	IP67 / IP68 / IP69k
----------------------	---------------------

Material

Contacts	CuSn / Au
----------	-----------

Contact surface	Au
-----------------	----

Body	TPU, black
------	------------

Cable	PUR
-------	-----

Slotted nut	Diecast zinc
-------------	--------------

Core insulation	PP
-----------------	----

Cable	fine-strand, flexible
-------	-----------------------

Sheath diameter	Ø 4.8 mm
-----------------	----------

Bending radius	> 10 x cable diameter, moving 5 x cable diameter, single bend
----------------	--

Color	grey
-------	------

Number of cores	4
-----------------	---

Core cross-section	0.34 mm ²
--------------------	----------------------

Conductor construction	19 x 0.15 mm Ø
------------------------	----------------

Shield	grid covering 85 %
--------	--------------------



Length	L	10 m
--------	---	------

Flammability

Contact carrier	94 HB
-----------------	-------

Housing	94 V-2
---------	--------

Connection Assignment



Accessories

	MH V1-SCREWDRIVER	torque screwdriver (0.6 Nm)
	MH V1-BIT M12	plug-in cap M12
	MH V1-Holder	Modular universal holder for M12 connectors
	V1/V3-LABELHOLDER	Label holder

Accessories

	V1/V3-LABEL	Label plate
	V1-MARKING-RING-BLUE	Marking ring for M12 connectors
	V1-MARKING-RING-GREEN	Marking ring for M12 connectors
	V1-MARKING-RING-ORANGE	Marking ring for M12 connectors
	V1-MARKING-RING-RED	Marking ring for M12 connectors
	V1-MARKING-RING-WHITE	Marking ring for M12 connectors
	V1-MARKING-RING-YELLOW	Marking ring for M12 connectors