



Model Number


V15SB-G-10M-PUR-ABG

Cable connector, M12, for PROFIBUS, 5-pin, PUR cable

Features

- Immunity to vibration, with mechanical latching
- Knurled nut suitable for tool assembly
- Gold plated contacts
- Suitable for 2-, 3- and 4-wire technology
- Halogen-free


Dimensions



Technical data

General specifications		
Number of pins		4 + shield
Connection 1		Male connector
Construction type 1		straight
Threading 1		M12
Connection 2		cable end
Electrical specifications		
Operating voltage	U _B	max. 48 V AC / 60 V DC
Operating current	I _B	max. 4 A
Volume resistance		< 5 mΩ
Ambient conditions		
Ambient temperature		Body: -40 ... 90 °C (-40 ... 194 °F) cable, flexing: -25 ... 80 °C (-13 ... 176 °F) cable, fixed: -40 ... 80 °C (-40 ... 176 °F)
Pollution degree		3
Mechanical specifications		
Contact elements		spring-loaded contact socket
Pin diameter		1 mm
Degree of protection		IP67
Material		
Contacts		CuSn / Au
Contact surface		Au
Body		TPU, black
Cable		PUR
Sleeve connector		Diecast zinc
Core insulation		PP
Cable		extra-fine wire, flexible
Sheath diameter		Ø 4.8 mm
Bending radius		> 10 x cable diameter, moving > 5 x cable diameter, fixed
Color		grey
Number of cores		5
Core cross-section		0.34 mm ²
Conductor construction		42 x 0.1 mm Ø
Shield		grid covering 85 %
Length	L	10 m
Flammability		
Contact carrier		HB
Housing		V-2
Compliance with standards and directives		
Standard conformity		
Specification		connector M12 x 1 : IEC 61076-2-101

Electrical connection



Release date: 2019-07-15 16:51 Date of issue: 2019-07-15 219108_eng.xml