




Cable socket, shielded V19-G-50M-PUR-A5S-PCV

- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Gold plated contacts
- Degree of protection IP67 / IP68 / IP69K
- Shield attached to coupling nut
- Halogen-free
- High flexibility
- For PCV SSI communication

Female cordset, M12, 8-pin, shielded, PUR cable



Technical Data

General specifications

Number of pins	8 + shield
Connection 1	socket
Construction type 1	straight
Threading 1	M12
Connection 2	cable end

Electrical specifications

Operating voltage	U_B	max. 60 V DC
Operating current	I_B	max. 2 A
Volume resistance		< 5 m Ω

Ambient conditions

Ambient temperature	-20 ... 80 °C (-4 ... 176 °F)
---------------------	-------------------------------

Mechanical specifications

Contact elements	spring-loaded contact socket
Pin diameter	1 mm
Degree of protection	IP67
Material	

Release date: 2020-06-12 Date of issue: 2020-06-12 Filename: 917121_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Technical Data

Contacts		CuSn / Au
Contact surface		Au
Body		TPU, black
Cable		PUR
Slotted nut		Diecast zinc
Core insulation		PP
Cable		fine-strand, flexible
Sheath diameter		Ø 6 mm
Bending radius		> 10 x cable diameter, moving > 5 x cable diameter, fixed
Color		grey
Cores		6 x 0.25 mm² twisted pairs
Conductor construction		19 x 0.13 mm Ø
Shield		Foil tinned copper braiding
Length	L	50 m
Drag chain suitability		
Drag chain cycles		min. 2000000
Motion velocity		max. 3 m/s
Acceleration		max. 10 m/s²
Torsional stress		± 360 °/m

Connection Assignment

