



Model Number


V19-G-BK10M-PVC-U/ABG-Y279548

Female cordset, M12, 8-pin, shielded, PVC cable

Features

- UL Recognized Component
- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Shield attached to coupling nut


Dimensions



Technical data

General specifications		
Number of pins		8 + shield
Connection 1		socket
Construction type 1		straight
Threading 1		M12
Connection 2		cable end
UL File Number		E231213
Electrical specifications		
Operating voltage	U _B	max. 30 V DC
Operating current	I _B	max. 2 A
Volume resistance		< 5 mΩ
Ambient conditions		
Ambient temperature		-40 ... 90 °C (-40 ... 194 °F) cable, fixed: -40 ... 80 °C (-40 ... 176 °F) cable, flexing: -20 ... 80 °C (-4 ... 176 °F)
Pollution degree		3
Mechanical specifications		
Contact elements		spring-loaded contact socket
Pin diameter		0,8 mm
Degree of protection		IP67
Material		
Contacts		CuSn / Au
Contact surface		Au
Body		TPU, black
Cable		PVC
Slotted nut		Diecast zinc
Core insulation		PVC
Cable		fine-strand, flexible
Sheath diameter		Ø 6.2 mm
Bending radius		> 15 x cable diameter, moving > 6 x cable diameter, fixed
Color		black
Number of cores		8
Core cross-section		0.25 mm ²
Conductor construction		14 x 0.15 mm Ø
Shield		grid covering 85 %
Length	L	10 m
Flammability		
Contact carrier		94 HB
Housing		94 V-2
Note		Labeling sleeve for the cable not included; with "Made in EU" imprint
Approvals and certificates		
UL approval		cURus AWM 20549 AWM I/II A/B 80°C 300V FT2 (cable)

Electrical connection



Release date: 2017-12-08 13:28 Date of issue: 2018-01-16 279548_eng.xml